



Aalto University
School of Engineering

Operation Management in Construction

Lecture #2 LBMS planning intro

Olli Seppänen
Associate professor


Topics, Lecture #2

- **Learning objectives of Lecture #2**
 - **LBMS planning overview**
 - **Interactive planning example (in contact session)**
 - **Production System risk**
 - **Production System cost**
 - **Planning case studies**
-
- **Introduction of Assignment #1: Production Planning assignment**

Intended learning objectives for this lecture

- ILO 2: **Students can compare and contrast** the similarities and differences of different production planning and control methods
 - *ILO emphasized for planning*
- ILO 3: **Students can calculate** the production system cost of a schedule
 - *ILO introduced: theory of production system cost*
- ILO 4: **Students can explain** the factors related to production system risk of a schedule
 - *ILO emphasized*
- ILO 5: **Students can explain** the significance of work and labor flow and how flow can be achieved in construction
 - *ILO introduced (planning)*
- ILO 9: **Students can analyze** the quality of a location-based schedule
 - *ILO introduced*

LBMS technical system



Location hierarchy

Project 1	
Quadrant	Floor
Center	Roof
	3
	2
	1
Northwest	Roof
	3
	2
	1
Northeast	Roof
	3
	2
	1
Southwest	Roof
	3
	2
	1
Southeast	Roof
	3
	2
	1

Project 2			
Building	Floor	Area	
Residential	7	B A	
	6	B A	
	5	B A	
	4	B A	
	3	B A	
	2	B A	
	1	B A	
	Basement	Garage	
	Office	9	B A
		8	B A
7		C B A	
6		C B A	
5		C B A	
4		C B A	
3		C B A	
2		C B A	
1		C B A	


Floor	Area
Tower Roof	STR C
Level 12	STR C
Tower Roof	STR B STR A
Level 12	STR B STR A
Level 11	STR C
Level 10	STR C
Level 09	STR C
Level 08	STR C
Level 11	STR B STR A
Level 10	STR B STR A
Level 09	STR B STR A
Level 08	STR B STR A
Level 04	STR F
Level 03	STR F
Level 02	STR F
Level 01	STR F
Level 03	STR E
Level 02	STR E
Level 01	STR E
Level 04	STR D
Level 03	STR D
Level 02	STR D
Level 01	STR D
Level 07	STR C
Level 06	STR C
Level 05	STR C
Level 04	STR C
Level 07	STR B STR A
Level 08	STR B STR A
Level 05	STR B STR A
Level 04	STR B STR A
Level 03	STR C
Level 02	STR C
Level 01	STR C
Level 03	STR B STR A
Level 02	STR B STR A
Level 01	STR B STR A

	2	3	4
		Level 4	Area C&D Area A&B
		Level 3	Area C&D Area A&B
[INT]	Level 2		Area C&D Area A&B
	Level 1		Area C&D Area A&B
	Lower Level		Area C&D Area A&B
	East B@3		COURTYARD
	South@3		South
[EXT]	West B@3		West B
	West A@3		West A
	North@3		North
	Level 4		Area D Area C Area B Area A
[SUP]	Level 3		Area D Area C Area B Area A
	Level 2		Area D Area C Area B Area A
	Level 1		
			Area D
			Area C
[SUB]	Lower Level		Area B
			Area A

Some LBS guidelines

- **Locations must be physical and clearly defined**
- **Top level locations**
 - Structurally independent sections (building / part of building) that can be completed as one entity
 - Separate buildings or separated by module lines / joints
- **Lowest level locations**
 - Small areas where only one **space-critical** task happens at the same time

Example of LBS of one floor



Quantities

- **Estimated by location**
 - Manually – time consuming
 - BIM-based – enables automated updates of quantities
- **Related quantity items can form a task IF the work**
 - Can be done at the same time in one location
 - Has the same logic outside the task
 - Can be completely finished in one location before moving to the next location

Location-based quantities

Same crew performs all items

Man-hours/unit

Section:

Floor:

Consumption

Code	Item	Man-hours/unit	Section: A					Section: B					Unit
			Floor: 1	2	3	4	Roof	1	2	3	4	Roof	
365116	Fit prefabricated balcony post units	2,25	7	7	7	7		7	7	7	7	5	NO
355125	Install room-size/square panels	1,8	8	1	1	1		10	1	1	1		NO
335107	Install precast concrete floor slabs	0,6		2	2	2	3		2	2	2	3	NO
345115	Install prefabricated staircases	1,98	1	1	1			1	1	1	1		NO
355115	Install load-bearing room-size/square panels	1,8	8	1	1	1		9	1	1	1	19	NO
335108	Install prefabricated beams	1		32	32	32	32		32	32	32	32	NO
365135	Fit prefabricated balcony roof units	0,62					5					5	NO
355145	Install thin-shell panels	1,8		17	17	17	19	17	17	17		19	NO
365125	Fit prefabricated balcony floor units	1,85		5	5	5			5	5	5		NO
325125	Top layer finishing to concrete floor slabs	1,84	14	6	6	6		14	6	6	6		NO
325115	Install precast dividing walls	1,84	10	15	15	15		16	16	16	16		NO
235150	Install precast concrete hollow core slabs	0,61	28					32					NO
Total man-hours			108	133	133	131	71	157	135	135	105	117	

Consumption rates and optimum crew


- **Building construction**

- Consumption rate in manhours / unit or machine hours / unit
 - *Consumption is the inverse of **productivity** (units / manhour)*
- Assumes **optimum crew**
 - *Minimum number of people working together to achieve optimum production*
 - *Several optimum crews can be deployed to increase **production rate** (units / day)*

- **Infrastructure / roads etc.**

- Typically more machines
- **Production rate** = units / day
- Each machine type can have a different production rate / day for the same work.


Which labor consumption to use?




- **”Effective time” 10-20% more than Method time**
 - **Includes ”normal” disruptions of less than 1 hr**
- **Total time T4, 10-30% more than Effective time**
- **= a lot of waste in productivity estimates!**



Source: Koskenvesa, Koskela et al. (2010)


From quantities to duration






- Defined position for any moment in time
- Production order (workflow)
- Hauling distances and directions
- Relocating resources
- Production halts
- Risk of overlapping tasks






Flowline Diagram – Overhead MEP




Flowline: graphical representation of movement of crews over time


Flowline Diagram




Flowline Diagram




Flowline Diagram – Continuous Flow




Flowline Diagram – Continuous Flow




Flowline Diagram – Continuous Flow




Flowline Diagram – Continuous Flow



Flowline Diagram – Continuous Flow




Flowline Diagram – Optimization




Decrease resources for
Metal Studs—slow down

Flowline Diagram – Optimization




Flowline Diagram – Optimization




Increase resources
for Finishes


Flowline Diagram – Optimization




Flowline Diagram - Buffers




Flowline Diagram - Buffers




Flowline Diagram - Buffers



Flowline Diagram - Buffers



Flowline Diagram - Buffers





Aalto University
School of Engineering

Video 2

Layered CPM Logic – elaborated in the contact session


Layer 1: Location-based link

Layer 2: Location-based on higher level

Layer 3: Internal links between locations

Layer 4: location lags

Layer 5: Random CPM links



Production system cost

Production system costs are functions of the schedule

- Direct labor costs
- Overhead costs

Measures the efficiency of the plan

- Better schedule – lower overall production system costs


Motivator for trade contractors to follow the plan

- Trade contractors pay for direct labor costs and any improvement in production system cost affects their bottom line


Production system cost components

- **Working time**
- **Mobilization / demobilization**
- **Waiting time**
- **Moving around**
- **Logistics**
- **Overhead**

Production system cost example



Calculation test



Production system risk


- **Construction has high variability**
 - Most of the variability is coming from external issues (70%)
 - Worker skills / work methods explain a small amount of variability (30%)
- **Variability can be analyzed with risk analysis. LBMS divides variability to:**
 - Variability in start dates
 - Variability in durations
 - Variability in productivity
 - Variability in resource availability
 - Variability caused by return delays

Design issues
Material logistics
Previous tasks
Weather
Resources
Communication

Work methods
Skill differences
Standardization

Optimum
productivity


Variability in start dates



T target: _____ Actual: Forecast: - - - -


Design mode
Schedule Planner v3.2.0.61564

Variability in durations




Design mode
Schedule Planner v3.2.0.61564

Variability in productivity




Design mode
Schedule Planner v3.2.0.61564

Variability of resource availability



Variability caused by return delays




Design mode
 Schedule Planner v3.2.0.61564

Buffers to protect against risk – capacity buffer


- **If variability / risks cannot be removed, buffers are needed**
 - **CAPACITY BUFFER is one way of buffering**
 - Plan with fewer resources than are available for the projectOR
 - Plan with lower production rate
 - **”Buffer resources” can work on non-critical tasks**
 - **Potential problem: setting goals low may result in low production (Parkinson’s law)**
-

Buffers to protect against risk – time buffer


- Time buffers can be added between tasks, construction phases or end of the project
- In LBMS, primarily between tasks
- Time buffers give time to react to deviations and prevent cascading delays
- However, they increase project duration




Planning example #1



Model-based Scheduling – 20 % duration compression



Planning example (Olivieri et al. 2018)



Thank you Questions & Comments