



Aalto University
School of Electrical
Engineering

ELEC-E8126: Robotic Manipulation Contacts and Manipulation

Ville Kyrki

22.2.2021

Learning goals

- Increase understanding and gain intuition on mechanics of manipulation.
- Understand the theory of form closure grasp planning.

Goal: Grasp planning

- Where an object needs to be grasped in order to perform a particular task?
 - In this context, where to place contacts on the object to immobilize it.
- Grasp analysis: Given information of contacts on an object (informal definition for *a grasp*), determine if the grasp is stable (immobilizes the object).

Recap: Single contact

- Impenetrability constraint

$$\mathbf{F}^T \mathbf{V} \geq 0$$

motion velocity twist

contact point


contact normal

$$\mathbf{F} = (\mathbf{p} \times \mathbf{n}, \mathbf{n})$$

- Motion constrained to half-plane
- $\mathbf{F}^T \mathbf{V} = 0$ if bodies remain in contact (to first-order, not considering curvature).


Several contacts in plane

- Can the object move? Around which point?




Several contacts in plane

- Geometrical approach (instant center of rotation)



Several contacts in plane

- Geometrical approach (instant center of rotation)




Contact constraints

- What are the feasible motions?

For each (not moving) contact:

$$F_i^T V \geq 0$$




$$F = (m_z, f_x, f_y) = ?$$

Motion constraints?


Contact constraints

- Contact constraints form a polyhedral convex cone



What happens if contacts immobilize object?

Form closure




- Form closure: a set of stationary contacts prevents all motions.
- Using first order analysis, impenetrability constraints are satisfied only by zero twist.
- Equivalently, contact wrenches span positively entire space.

$$F_i^T V \geq 0$$


$$\left\{ \sum_i k_i F_i \mid k_i \geq 0 \right\} = R^6 \quad \leftarrow \text{linear prog. sol.}$$

- Higher-order analysis may provide form closure even without above constraints (curved surfaces).



Quality of a grasp

- Is one of these grasps better? Why?



Grasp quality metrics

- Grasp metric (Q): A number calculated based on contact wrenches so that $Q < 0$ indicates not stable and larger positive values indicate better grasps.
- Typical idea: How big external disturbances a grasp can withstand.
- Information about tasks or expected disturbances can be used.

Worst case quality without prior information

- Set of possible wrenches:

$$CF = \left\{ \sum_i k_i \mathbf{F}_i \mid 0 \leq k_i \leq f_{max} \right\} = R^6$$





maximum force per contact

- What's the largest ball that fits inside polytope CF?





smallest external force that breaks grasp

- Practical notes

- scale moments (torques) by characteristic length of object
- origin at object CoM



Which one is better?



Sampling based grasp planning

- Now that we have a metric, how to plan a grasp?
 - Sampling
 - Choose candidate contacts
 - Evaluate resulting grasp
 - More about grasp planning next week
- Or optimize numerically (e.g. simulated annealing).

Summary

- Form closure means that the form of stationary contacts prevents motion.
- Impenetrability constraints can be used to analyze feasible motions.
- Grasps can be planned by maximizing grasp quality metrics.

Next time: Manipulation and friction

- Contacts with friction
- State-of-the-art in grasp planning
- Readings:
 - Lynch & Park, Chapter 12.2-12.2.2