

Package ‘tsDyn’

February 4, 2020

Type Package

Title Nonlinear Time Series Models with Regime Switching

Version 10-1.2

Date 2020-02-04

Author Antonio Fabio Di Narzo [aut],
Jose Luis Aznarte [ctb],
Matthieu Stigler [aut],
Ho Tsung-wu [cre]

Maintainer Ho Tsung-wu <tsungwu@ntnu.edu.tw>

Depends R (>= 3.5.0)

Imports mnormt, mgcv, nnet, tseriesChaos, tseries, utils, vars, urca,
forecast, MASS, Matrix, foreach, methods

Suggests sm, scatterplot3d, rgl

Description Implements nonlinear autoregressive (AR) time series models. For univariate series, a non-parametric approach is available through additive nonlinear AR. Parametric modeling and testing for regime switching dynamics is available when the transition is either direct (TAR: threshold AR) or smooth (STAR: smooth transition AR, LSTAR). For multivariate series, one can estimate a range of TVAR or threshold cointegration TVECM models with two or three regimes. Tests can be conducted for TVAR as well as for TVECM (Hansen and Seo 2002 and Seo 2006).

License GPL (>= 2)

URL <http://github.com/MatthieuStigler/tsDyn/wiki>

NeedsCompilation yes

Repository CRAN

Date/Publication 2020-02-04 10:20:02 UTC

R topics documented:

tsDyn-package	3
aar	4
accuracy_stat	5

addRegime	6
autopairs	7
autotriples	8
autotriples.rgl	9
availableModels	10
barry	10
BBCTest	11
coefB	12
delta	14
delta.lin	15
extendBoot	16
fevd	17
fitted.nlVar	18
getTh	19
IIPUs	20
irf	21
isLinear	23
KapShinTest	24
lags.select	25
LINEAR	26
lineVar	27
llar	29
logLik.nlVar	31
logLik.VECM	33
LSTAR	34
m.unrate	36
MakeThSpec	37
MAPE	38
mse	39
nlar methods	40
NNET	41
plot methods	42
predict.nlar	44
predict.TVAR	46
predict_rolling	47
rank.select	49
rank.test	51
regime	53
resVar	54
selectHyperParms	55
selectSETAR	57
SETAR	59
setar.sim	61
setarTest	63
sigmoid	65
STAR	65
toLatex.setar	66
TVAR	67

TVAR.LRtest	69
TVAR.sim	71
TVECM	73
TVECM.HStest	76
TVECM.SeoTest	78
UsUnemp	80
VAR.sim	80
VARrep	82
VECM	83
VECM.sim	85
VECM_symbolic	88
zeroyld	89

Index	91
--------------	-----------

tsDyn-package	<i>Getting started with the tsDyn package</i>
---------------	---

Description

Getting started with the tsDyn package

Details

This package provide some tools inspired by nonlinear dynamics for the analysis-modelling of observed time series.

For loading the package, type:

```
library(tsDyn)
```

A good place to start learning the package usage, is the vignette. It contains a more detailed guide on package contents, and an applied case study. At the R prompt, write:

```
vignette("tsDyn")
```

For a full list of functions exported by the package, type:

```
ls("package:tsDyn")
```

There is also an experimental GUI for built-in NLAR models. Call it with:

```
nlarDialog(timeSeries)
```

where `timeSeries` is an available time series object.

Each exported function has a corresponding man page (some man pages are in common to more functions). Display it by typing

```
help(functionName)
```

Author(s)

Antonio, Fabio Di Narzo

See Also

[availableModels](#) for listing all currently available NLAR models
[autopairs, autotriples, autotriples.rgl](#) for graphical explorative functions
[llar, delta, delta.lin](#) for nonlinearity checking tools

aar

*Additive nonlinear autoregressive model***Description**

Additive nonlinear autoregressive model.

Usage

```
aar(x, m, d=1, steps=d, series)
```

Arguments

x	time series
m, d, steps	embedding dimension, time delay, forecasting steps
series	time series name (optional)

Details

Nonparametric additive autoregressive model of the form:

$$x_{t+s} = \mu + \sum_{j=1}^m s_j(x_{t-(j-1)d})$$

where s_j are nonparametric univariate functions of lagged time series values. They are represented by cubic regression splines. s_j are estimated together with their level of smoothing using routines in the **mgcv** package (see references).

Value

An object of class `nlar`, subclass `aar`, i.e. a list with mostly internal structures for the fitted [gam](#) object.

Author(s)

Antonio, Fabio Di Narzo

References

Wood, *mgcv*:GAMs and Generalized Ridge Regression for R. *R News* 1(2):20-25 (2001)
 Wood and Augustin, GAMs with integrated model selection using penalized regression splines and applications to environmental modelling. *Ecological Modelling* 157:157-177 (2002)

Examples

```
#fit an AAR model:
mod <- aar(log(lynx), m=3)
#Summary informations:
summary(mod)
#Diagnostic plots:
plot(mod)
```

accuracy_stat	<i>Forecasting accuracy measures.</i>
---------------	---------------------------------------

Description

Compute forecasting accuracies. This is very similar of the [accuracy](#) method form **forecast**.

Usage

```
accuracy_stat(object, ...)

## Default S3 method:
accuracy_stat(object, true, ...)

## S3 method for class 'pred_roll'
accuracy_stat(object, w, ...)
```

Arguments

object	A data-frame, matrix, or object of class <code>pred_roll</code>
...	Not used currently.
true	If object is just a matrix or data-frame, true values to be compared to should be supplied
w	Optional. For objects of class <code>pred_roll</code> containing multiple variables, user can specify the way to aggregate the specific x-step-ahead into the 'all' category

Details

The function works either for a simple data.frame or for objects `pred_roll`. For simple data.frames, the argument `true`, i.e. a data frame containing the true values, has to be provided. For `pred_roll` objects, the true values are contained in the object, so no need (nor possibility) to provide the true values.

Value

A data-frame containing the forecasting accuracy measures.

Author(s)

Matthieu Stigler

Examples

```
## univariate:
mod_ar <- linear(lynx[1:100], m=1)
mod_ar_pred <- predict_rolling(mod_ar, newdata=lynx[101:114])
accuracy_stat(object=mod_ar_pred$pred, true=mod_ar_pred$true)

## multivariate
data(barry)
mod_var <- lineVar(barry, lag=1)

mod_var_pred <- predict_rolling(object=mod_var, nroll=10, n.ahead=1:3)
accuracy_stat(object=mod_var_pred)
accuracy_stat(object=mod_var_pred, w=c(0.7, 0.2, 0.1))
```

addRegime	<i>addRegime test</i>
-----------	-----------------------

Description

addRegime test

Usage

```
addRegime(object, ...)
```

Arguments

object	fitted model object with at least 2 regimes
...	arguments to and from other methods

Value

A list containing the p-value of the F statistic and a boolean, true if there is some remaining nonlinearity and false otherwise.

Author(s)

J. L. Aznarte

References

TODO

See Also[star](#)**Examples**

```
##TODO
```

autopairs

Bivariate time series plots

Description

Bivariate time series plots: scatterplots, directed lines and kernel density estimations using functions in the **sm** package.

Usage

```
autopairs(x, lag = 1, h, type = c("levels", "persp", "image", "lines",  
  "points", "regression"))
```

Arguments

x	time series
lag	time lag
h	kernel window (useful only for kernel estimations)
type	type of plot: contour levels, perspective plots, image, directed lines, points or points with superposed kernel regression

Details

Bivariate time series plots: scatterplots, directed lines and kernel density and regression functions estimations using functions in the package **sm**. In particular, for kernel density estimation [sm.density](#) is used, with smoothing parameter h defaulting to [hnorm](#). For kernel regression, [sm.regression](#) is used.

Value

None. Plots are produced on the default graphical device.

Author(s)

Wrappers to **sm** by Antonio, Fabio Di Narzo

See Also

For finer control on density estimation, consider using directly [sm.density](#) and, especially, [sm.ts.pdf](#) from package **sm**.

Examples

```
x <- log10(lynx)
autopairs(x, lag=2, type="lines")
```

autotriples

Trivariate time series plots

Description

Trivariate time series plots: kernel autoregression using functions in the **sm** package

Usage

```
autotriples(x, lags = 1:2, h, type = c("levels", "persp", "image", "lines",
  "points"))
```

Arguments

x	time series
lags	vector of regressors lags
h	kernel window
type	type of plot: contour levels, perspective plots, image

Details

This function displays trivariate time series plots, i.e. kernel regression of $x[t - lags[1]], x[t - lags[2]]$ against $x[t]$ using functions in the package **sm**. In particular, [sm.regression](#) is used, with smoothing parameter defaulting to [hnorm\(x\)](#).

Value

None. Plots are produced on the default graphical device.

Author(s)

Wrappers to **sm** by Antonio, Fabio Di Narzo

See Also

For finer control on kernel regression, consider using directly [sm.regression](#) and, especially, [sm.autoregression](#) in package **sm**.

Examples

```
autotriples(log(lynx))
autotriples(log(lynx), type="persp")
autotriples(log(lynx), type="image")
```

autotriples.rgl *Interactive trivariate time series plots*

Description

Interactive trivariate time series plots

Usage

```
autotriples.rgl(x, lags = 1:2, type = c("lines", "points"))
```

Arguments

x	time series
lags	vector of regressors lags
type	type of plot: contour levels, perspective plots, image

Details

This function displays interactive trivariate time series plots $x[t-lags[1]]$, $x[t-lags[2]]$ against $x[t]$ using the interactive [rgl](#) device.

Value

None. A plot is produced on the current [rgl](#) device.

Author(s)

Wrapper to 'sm' and GUI by Antonio, Fabio Di Narzo

See Also

[autotriples](#) for 3d visualization via **scatterplot3d** package and for kernel post-processing of the cloud for nonparametric autoregression functions estimates.

Examples

```
if(interactive())
  autotriples.rgl(log(lynx))
```

availableModels *Available models*

Description

Available built-in time series models

Usage

```
availableModels()
```

Details

Return the list of built-in available ‘nlar’ time series models

Value

A character vector containing built-in time series models. For help on a specific model, type: `help(modelName)`.

Author(s)

Antonio, Fabio Di Narzo

Examples

```
availableModels()
```

barry *Time series of PPI used as example in Bierens and Martins (2010)*

Description

This data set contains the series used by *Bierens and Martins* for testing for PPI between Canada and US.

Usage

```
data(barry)
```

Format

A data frame with 324 monthly observations, ranging from 1973:M1 until 1999:M12.

dolcan	Exchange rate US/Can dollar.
cpiUSA	US Consumer Price Index.
cpiCAN	Canada Consumer Price Index.

Author(s)

Matthieu Stigler

Source

Bierens, H. and Martins, L. (2010), Time Varying Cointegration,

BBCTest	<i>Test of unit root against SETAR alternative</i>
---------	--

Description

Test of unit root against a stationnary three regime SETAR alternative

Usage

```
BBCTest(x, m, series, testStat = c("LR", "Wald", "LM"), trim = 0.1,
        grid = c("minPerc", "minObs"))
```

Arguments

x	time series
m	Number of lags under the alternative
series	time series name (optional)
testStat	Type of test statistic to use
trim	trimming parameter indicating the minimal percentage of observations in each regime
grid	Whether a minimal number of percentage or observations should be imposed. See details

Details

TODO

Value

A object of class "BBC2004Test" containing:

- The value of the sup Test
- The version of test used (either Wald, LM or LR).

Author(s)

Matthieu Stigler

See Also

[setarTest](#) for a test with stationarity as a null.

Examples

```
BBCTest(lynx, m=3, test="Wald", grid="minPerc")
```

coefB

Extract cointegration parameters A, B and PI

Description

Extract parameters in VECM: adjustment coefficients A, cointegrating coefficients B , or the composite matrix PI

Usage

```
coefB(object, ...)

## S3 method for class 'VECM'
coefB(object, ...)

## S3 method for class 'ca.jo'
coefB(object, r = 1, normalize = TRUE, ...)

coefA(object, ...)

## S3 method for class 'VECM'
coefA(object, ...)

## S3 method for class 'ca.jo'
coefA(object, r = 1, normalize = TRUE, ...)

coefPI(object, ...)
```

Arguments

object	An object of class <code>VECM</code> , <code>ca.jo</code>
r	The cointegrating rank
normalize	Whether to normalize the A/B coefficients. See details
...	Further arguments passed to methods

Details

The functions extract the parameters from a VECM with K variables and rank r :

A Adjustment coefficients, of dim $K \times r$

B Cointegrating coefficients, of dim $K \times r$

Pi Matrix $\Pi = AB'$, of dim $K \times K$

Coefficients are extracted from a VECM in package `tsDyn`, or from a VECM obtained in package `urca` from `ca.jo` or `cajorls`.

Note that by default, the A and B coefficients returned are normalized (see below). This is the case for results obtained from `VECM/lineVar` and `cajorls`, while for `ca.jo`, the user has the choice (but `normalize=TRUE` by default), in which case the rank r is also to be specified. The normalization is the Phillips triangular representation, as suggested by Johansen (1995, p. 72), standardising the first $r \times r$ coefficients to I_r :

$$\mathbf{B} \ B_{norm} = B(c' B)^{-1} \text{ with } c = (I_r, 0_{p-r,r})'$$

$$\mathbf{A} \ A_{norm} = B' c$$

Finally, note that the function also apply to objects obtained from tests of class `ca.jo.test` (from `blrtest` etc...). Care should be taken however, since the normalization might override the restrictions imposed.

Value

A matrix containing the coefficients

Author(s)

Matthieu Stigler

Examples

```
data(barry)
vecm <- VECM(barry, lag=1, estim="ML")
vecm_r2 <- VECM(barry, lag=1, estim="ML", r=2)

## extract coefficients:
coefA(vecm)
coefB(vecm)
coefPI(vecm)
coefB(vecm_r2)
coefPI(vecm_r2)
```

```

## Beta-Restricted VECM:
beta_vecm2 <- coefB(vecm_r2)
beta_vecm2[3,2] <- 0.02
vecm_r2_rest <- VECM(barry, lag=1, estim="ML", r=2, beta=beta_vecm2)
round(coefB(vecm_r2_rest),5)

## Package vars/urca
if(require(urca)){
  vecm_ur <- ca.jo(barry, K=2)
  coefB(vecm_ur)
  coefB(vecm_ur,r=2)
  coefB(cajorls(vecm_ur, r=2))
  all.equal(coefB(vecm), coefB(vecm_ur), check.attributes=FALSE)
  all.equal(coefB(vecm_r2), coefB(vecm_ur, r=2), check.attributes=FALSE)
}

```

delta

delta test of conditional independence

Description

delta statistic of conditional independence and associated bootstrap test

Usage

```
delta(x, m, d = 1, eps)
```

```
delta.test(x, m = 2:3, d = 1, eps = seq(0.5 * sd(x), 2 * sd(x), length =
4), B = 49)
```

Arguments

x	time series
m	vector of embedding dimensions
d	time delay
eps	vector of length scales
B	number of bootstrap replications

Details

delta statistic of conditional independence and associated bootstrap test. For details, see Manzan(2003).

Value

delta returns the computed delta statistic. delta.test returns the bootstrap based 1-sided p-value.

Warning

Results are sensible to the choice of the window `eps`. So, try the test for a grid of `m` and `eps` values. Also, be aware of the curse of dimensionality: `m` can't be too high for relatively small time series. See references for further details.

Author(s)

Antonio, Fabio Di Narzo

References

Sebastiano Manzan, Essays in Nonlinear Economic Dynamics, Thela Thesis (2003)

See Also

BDS marginal independence test: [bds.test](#) in package **tseries**

Teraesvirta's neural network test for nonlinearity: [terasvirta.test](#) in package **tseries**

delta test for nonlinearity: [delta.lin.test](#)

Examples

```
delta(log10(lynx), m=3, eps=sd(log10(lynx)))
```

delta.lin

delta test of linearity

Description

delta test of linearity based on conditional mutual information

Usage

```
delta.lin(x, m, d = 1)
```

```
delta.lin.test(x, m = 2:3, d = 1, eps = seq(0.5 * sd(x), 2 * sd(x), length  
= 4), B = 49)
```

Arguments

<code>x</code>	time series
<code>m</code>	vector of embedding dimensions
<code>d</code>	time delay
<code>eps</code>	vector of length scales
<code>B</code>	number of bootstrap replications

Details

delta test of linearity based on conditional mutual information

Value

delta.lin returns the parametrically estimated delta statistic for the given time series (assuming linearity). delta.lin.test returns the bootstrap based 1-sided p-value. The test statistic is the difference between the parametric and nonparametric delta estimators.

Author(s)

Antonio, Fabio Di Narzo

References

Sebastiano Manzan, Essays in Nonlinear Economic Dynamics, Thela Thesis (2003)

Examples

```
delta.lin(log10(lynx), m=3)
```

extendBoot

extension of the bootstrap replications

Description

This function updates an existing bootstrap test with new bootstrap replications.

Usage

```
extendBoot(x, nboot)
```

Arguments

x	A object from setarTest (hence of class Hansen99Test)
nboot	The number of new bootstrap replications

Details

The plot function will draw the old and new distribution, hence allowing to test the sensitivity of the results obtained.

Value

Returns an object of the same class with same objects but updated values.

Author(s)

Matthieu Stigler

See Also[BBCTest](#) for a similar test. [setarTest](#) for a test with stationarity as a null.**Examples**

```
## Not run:
# test with 10 bootstrap replications:
a<-setarTest(sun[1:100], m=1, nboot=10)
plot(a)

#use old results and compute 20 new replications
b<-extendBoot(a, n=20)
#see the different distributions:
plot(b)

## End(Not run)
```

fevd

Forecast Error Variance Decomposition

Description

Use the fevd function from package **vars** to compute the forecast error variance decomposition of a VAR(p) or VECM for n. ahead steps.

Usage

```
## S3 method for class 'nlVar'
fevd(x, n.ahead=10, ...)
```

Arguments

x	Object of class 'VAR' generated by <code>lineVar()</code> , or an object of class 'VECM' generated by <code>VECM()</code> .
n.ahead	Integer specifying the number of steps.
...	Currently not used.

Details

The function converts the VAR or VECM computed by package `tsDyn` into an object of class 'vec2var', on which then the `fevd` method is applied. For details, see package **vars**.

Value

A list with class attribute 'varfevd' of length K holding the forecast error variances as matrices.

Author(s)

Bernhard Pfaff

References

Hamilton, J. (1994), *Time Series Analysis*, Princeton University Press, Princeton.

LÃ¼tkepohl, H. (2006), *New Introduction to Multiple Time Series Analysis*, Springer, New York.

See Also

[plot](#) for the plot method. [lineVar](#), [VECM](#) for the models.

Examples

```
data(zeroyld)
mod_vecm <- VECM(zeroyld, lag = 2)
fevd(mod_vecm, n.ahead = 5)
```

fitted.nlVar

fitted method for objects of class nlVar, i.e. VAR and VECM models.

Description

Returns the fitted values of the model, either as computed in the model, or back to the original series level.

Usage

```
## S3 method for class 'nlVar'
fitted(object, level = c("model", "original"), ...)
```

Arguments

object	An object of class 'nlVar'; generated by VECM or lineVar .
level	How to return the fitted values. See below.
...	Currently not used.

Details

In case of a VAR in differences, in ADF specification, or a VECM, the fitted values are actually in differences. With the option level="original", the function returns the series in the original level.

For VAR in levels, the two arguments are evidently the same and hence it is not taken into account, returning a warning.

Value

A matrix.

Author(s)

Matthieu Stigler

Examples

```
## estimate models
data(barry)

ve <- VECM(barry, lag=2)
va <- lineVar(barry, lag=1)
va_diff <- lineVar(barry, lag=1, I="diff")
va_ADF <- lineVar(barry, lag=1, I="ADF")

## get fitted values:
tail(fitted(ve))
tail(fitted(ve, level="original"))

tail(fitted(va))
tail(fitted(object=va, level="original"))

tail(fitted(va_diff))
tail(fitted(object=va_diff, level="original"))

tail(fitted(va_ADF))
tail(fitted(object=va_ADF, level="original"))
```

getTh

Extract threshold(s) coefficient

Description

Extract threshold coefficient(s)

Usage

```
getTh(object, ...)
```

```
## Default S3 method:
getTh(object, ...)
```

Arguments

object object of class setar, summary.setar, nlVar
... additional arguments to getTh

Value

Threshold value.

Author(s)

Matthieu Stigler

Examples

```
set<-setar(lynx, m=3)
getTh(set)
#getTh(summary(set))
```

IIPUs

US monthly industrial production from Hansen (1999)

Description

This data, used as example in Hansen (1999), contains the US monthly industrial production.

Usage

```
data(IIPUs)
```

Format

A monthly time series of class ts starting in January 1960 and ending in September 1997. Note that the series ends at 1997 and not 1998 as in the paper of Hansen, even if the data was taken from his site and the graph is exactly the same.

Source

Hansen (1999) Testing for linearity, Journal of Economic Surveys, Volume 13, Number 5, December 1999, pp. 551-576(26) available at: <http://www.ssc.wisc.edu/~bhansen/papers/cv.htm>

Examples

```

data(IIPUs)
end(IIPUs) #not same date as in the paper
plot(IIPUs)#exactly same graph as in the paper
sel<-selectSETAR(IIPUs, m=16, thDelay=5, criterion="SSR", trim=0.1, plot=FALSE)
sel #R function obtains a lower SSR with another threshold
plot(sel)
setar(IIPUs, m=16, thDelay=5, trim=0.1, th=sel$th)

sel2<-selectSETAR(IIPUs, m=16, thDelay=5, criterion="SSR", trim=0.1, plot=FALSE, nthresh=2)
sel2
#all results agree
set2<-setar(IIPUs, m=16, thDelay=5, th=sel2$th, trim=0.1)
#most of the results agree, except constant in the low regime which has opposed signs!
summary(set2)

#this is obviously a error in Hansen, see:
XX<-embed(IIPUs, 17)
Y<-XX[,1]
X<-XX[,-1]
dummyDown<-ifelse(X[,6]<= -2.5, 1,0)
sum(dummyDown)
M<-cbind(1*dummyDown,X*dummyDown )
lm(Y~M-1)

## see the test functions (not run, due to long computing time, even with small nboot
## Not run:
setarTest(IIPUs, m=16, thDelay=5, nboot=10, check=TRUE)
#because of the discrepancy. test1vs2 does not correspond, test 1vs3 conforms
setarTest(IIPUs, m=16, thDelay=5, nboot=10, check=TRUE, test="2vs3")
#test 2vs3 is also different of the version in the article (27)

## End(Not run)

```

 irf

Impulse response function

Description

Use the fevd function from package **vars** to compute the impulse response coefficients of a VAR(p) (or transformed VECM to VAR(p)) for n.ahead steps.

Usage

```

## S3 method for class 'nlVar'
irf(x, impulse = NULL, response = NULL, n.ahead = 10,
ortho = TRUE, cumulative = FALSE, boot = TRUE, ci = 0.95,
runs = 100, seed = NULL, ...)

```

Arguments

x	Object of class 'VAR'; generated by <code>lineVar()</code> , or object of class 'VECM'; generated by <code>VECM()</code> .
impulse	A character vector of the impulses, default is all variables.
response	A character vector of the responses, default is all variables.
n.ahead	Integer specifying the steps.
ortho	Logical, if TRUE (the default) the orthogonalised impulse response coefficients are computed (only for objects of class 'varest').
cumulative	Logical, if TRUE the cumulated impulse response coefficients are computed. The default value is false.
boot	Logical, if TRUE (the default) bootstrapped error bands for the impulse response coefficients are computed.
ci	Numeric, the confidence interval for the bootstrapped errors bands.
runs	An integer, specifying the runs for the bootstrap.
seed	An integer, specifying the seed for the rng of the bootstrap.
...	Currently not used.

Details

The function converts the VAR or VECM computed by package `tsDyn` into an object of class 'vec2var', on which then the `irf` method is applied. For details, see the relevant package.

Value

A list of class 'varirf' with the following elements is returned:

irf	A list with matrices for each of the impulse variables containing the impulse response coefficients.
Lower	If <code>boot = TRUE</code> , a list with matrices for each of the impulse variables containing the lower bands.
Upper	If <code>boot = TRUE</code> , a list with matrices for each of the impulse variables containing the upper bands.
response	Character vector holding the names of the response variables.
impulse	Character vector holding the names of the impulse variables.
ortho	Logical, if TRUE, orthogonalised impulse responses have been computed.
cumulative	Logical, if TRUE, cumulated impulse responses have been computed.
runs	An integer, specifying the number of bootstrap runs.
ci	Numeric, defining the confidence level.
boot	Logical, if TRUE bootstrapped error bands have been computed.
model	Character, containing 'class(x)'.

Author(s)

Bernhard Pfaff

References

Efron, B. and R. J. Tibshirani (1993), *An Introduction to the Bootstrap*, Chapman & Hall, New York.

Hamilton, J. (1994), *Time Series Analysis*, Princeton University Press, Princeton.

Lütkepohl, H. (2006), *New Introduction to Multiple Time Series Analysis*, Springer, New York.

See Also

[plot](#) for the plot method. [lineVar](#), [VECM](#) for the models.

Examples

```
data(barry)

## For VAR
mod_var <- lineVar(barry, lag = 2)
irf(mod_var, impulse = "dolcan", response = c("dolcan", "cpiUSA", "cpiCAN"), boot =
FALSE)

## For VECM
mod_VECM <- VECM(barry, lag = 2, estim="ML", r=2)
irf(mod_VECM, impulse = "dolcan", response = c("dolcan", "cpiUSA", "cpiCAN"), boot =
FALSE)
```

isLinear

isLinear

Description

Generic NLAR linearity test

Usage

```
isLinear(object, ...)
```

Arguments

object	fitted time series model
...	arguments to and from other methods

Author(s)

A. F. Di Narzo

KapShinTest

Test of unit root against SETAR alternative with

Description

Test of unit root against a stationary 3 regime SETAR alternative with random walk in the inner regime

Usage

```
KapShinTest(x, m=1, series, include = c("none", "const", "trend", "both"),
            c=3, delta=0.5, points=NULL, minObsMid=10,
            trick=c("for", "apply", "mapply"), trace=FALSE)
```

Arguments

x	time series
m	Number of lags under the alternative
series	time series name (optional)
include	Whether data should be raw, de-meanned or de-meanned and de-trended
c	Argument for the grid search. See details
delta	Argument for the grid search. See details
points	Points for the grid search. See details
minObsMid	Minimal number of observations in the inner regime
trick	type of internal function used
trace	should additional infos be printed? (logical)

Details

This function is currently spurious.

Value

A object of class KapShin2006Test containing:

statistic	The three (SupW, AvgW, ExpW) test statistics computed
case	Whether the data was transformed, corresponds to input argument include
series	The name of the series

Author(s)

Matthieu Stigler

See Also

[BBCTest](#) for a similar test. [setarTest](#) for a test with stationarity as a null.

Examples

```
KapShinTest(lynx, m=1, trace=FALSE, include="none", points=10)
```

lags.select

Selection of the lag with Information criterion.

Description

Selection of the cointegrating rank and the lags with Information criterion (AIC, BIC).

Usage

```
lags.select(data, lag.max = 10, include = c("const", "trend", "none",
      "both"), fitMeasure = c("SSR", "LL"), sameSample = TRUE)
```

Arguments

data	multivariate time series.
lag.max	Maximum number of lags to investigate.
include	Type of deterministic regressors to include.
fitMeasure	Whether the AIC/BIC should be based on the full likelihood, or just the SSR. See explanations in logLik.VECM .
sameSample	Logical. Whether the data should be shortened so that the AIC/BIC are estimated on the same sample. Default to TRUE.

Details

This function selects the lag according to AIC, BIC and Hannan-Quinn.

Value

An object of class [rank.select](#), with ‘print’ and ‘summary methods’, containing among other the matrices of AIC/BIC/HQ.

Author(s)

Matthieu Stigler

See Also

[rank.select](#), the underlying function, to estimate the rank also.

[VARselect](#) in package **vars**, does basically the same.

Examples

```
data(barry)

#
rk_sel <- lags.select(barry)
rk_sel
#summary(rk_sel)
```

 LINEAR

Linear AutoRegressive models

Description

AR(m) model

Usage

```
linear(x, m, d=1, steps=d, series, include = c("const", "trend", "none", "both"),
       type=c("level", "diff", "ADF"))
```

Arguments

x	time series
m, d, steps	embedding dimension, time delay, forecasting steps
series	time series name (optional)
include	Type of deterministic regressors to include
type	Whether the variable is taken is level, difference or a mix (diff y= y-1, diff lags) as in the ADF test

Details

AR(m) model:

$$x_{t+s} = \phi_0 + \phi_1 x_t + \phi_2 x_{t-d} + \dots + \phi_m x_{t-(m-1)d} + \epsilon_{t+s}$$

Value

A `nlar` object, `linear` subclass.

Author(s)

Antonio, Fabio Di Narzo

See Also

[nlar](#) for fitting this and other models to time series data

Examples

```
#fit an AR(2) model
mod.linear <- linear(log(lynx), m=2)
mod.linear
#summary(mod.linear)
```

lineVar

Multivariate linear models: VAR and VECM

Description

Estimate either a VAR or a VECM.

Usage

```
lineVar(data, lag, r = 1, include = c("const", "trend", "none", "both"),
  model = c("VAR", "VECM"), I = c("level", "diff", "ADF"), beta = NULL,
  estim = c("2OLS", "ML"), LRinclude = c("none", "const", "trend", "both"),
  exogen = NULL)
```

Arguments

data	multivariate time series (first row being first=oldest value)
lag	Number of lags to include in each regime
r	Number of cointegrating relationships
include	Type of deterministic regressors to include
model	Model to estimate. Either a VAR or a VECM
I	For VAR only: whether in the VAR the variables are to be taken in levels (original series) or in difference, or similarly to the univariate ADF case.
beta	for VECM only: user-specified cointegrating value. If NULL, will be estimated using the estimator specified in estim
estim	Type of estimator for the VECM: '2OLS' for the two-step approach or 'ML' for Johansen MLE
LRinclude	Possibility to include in the long-run relationship and the ECT a trend, a constant, etc. Can also be a matrix with exogenous regressors
exogen	Inclusion of exogenous variables (first row being first=oldest value). Is either of same size than data (then automatically cut) or than end-sample.

Details

This function provides basic functionalities for VAR and VECM models. More comprehensive functions are in package **vars**. A few differences appear in the VECM estimation:

Engle-Granger estimator The Engle-Granger estimator is available

Presentation Results are printed in a different ways, using a matrix form

lateX export The matrix of coefficients can be exported to latex, with or without standard-values and significance stars

Two estimators are available: the Engle-Granger two-steps approach (2OLS) or the Johansen (ML). For the 2OLS, deterministic regressors (or external variables if `LRinclude` is of class numeric) can be added for the estimation of the cointegrating value and for the ECT. This is only working when the beta value is not pre-specified.

The argument `beta` is only for **VECM**, look at the specific help page for more details.

Value

Fitted model data

Author(s)

Matthieu Stigler

See Also

VECM which is just a wrapper for `lineVar(...,model="VECM")`. Methods `predict.VAR`, `VARrep`, `regime`, `irf` and `toLatex`.

TVAR and **TVECM** for the corresponding threshold models. `linear` for the univariate AR model.

Examples

```
data(zeroyld)

#Fit a VAR
VAR <- lineVar(zeroyld, lag=1)
VAR
#summary(VAR)

#compare results with package vars:
if(require(vars)) {
  a<-VAR(zeroyld, p=1)
  coef_vars <- t(sapply(coef(a), function(x) x[c(3,1,2),1]))
  all.equal(coef(VAR),coef_vars, check.attributes=FALSE)
}

###VECM
VECM.EG <- lineVar(zeroyld, lag=2, model="VECM")
VECM.EG
#summary(VECM.EG)
```

```

VECM.ML <- lineVar(zeroyld, lag=2, model="VECM", estim="ML")
VECM.ML
#summary(VECM.ML)

###Check Johansen MLE
myVECM <- lineVar(zeroyld, lag=1, include="const", model="VECM", estim="ML")
myVECM
#summary(myVECM, digits=7)

#comparing with vars package
if(require(vars)){
a<-ca.jo(zeroyld, spec="trans")
a
#summary(a)
#same answer also!
}

##export to Latex
#toLatex(VECM.EG)
#toLatex(summary(VECM.EG))
options("show.signif.stars"=FALSE)
#toLatex(summary(VECM.EG), parenthese="Pvalue")
options("show.signif.stars"=TRUE)

```

llar

Locally linear model

Description

Casdagli test of nonlinearity via locally linear forecasts

Usage

```
llar(x, m, d = 1, steps = d, series, eps.min = sd(x)/2,
eps.max = diff(range(x)), neps = 30, trace = 0)
```

```
llar.predict(x, m, d=1, steps=d, series, n.ahead=1,
eps=stop("you must specify a window value"),
onvoid=c("fail","enlarge"), r = 20, trace=1)
```

```
llar.fitted(x, m, d=1, steps=d, series, eps, trace=0)
```

Arguments

<code>x</code>	time series
<code>m, d, steps</code>	embedding dimension, time delay, forecasting steps
<code>series</code>	time series name (optional)
<code>n.ahead</code>	n. of steps ahead to forecast
<code>eps.min, eps.max</code>	min and max neighbourhood size
<code>neps</code>	number of neighbourhood levels along which iterate
<code>eps</code>	neighbourhood size
<code>onvoid</code>	what to do in case of an isolated point: stop or enlarge neighbourhood size by an <code>r%</code>
<code>r</code>	if an isolated point is found, enlarge neighbourhood window by <code>r%</code>
<code>trace</code>	tracing level: 0, 1 or more than 1 for <code>llar</code> , 0 or 1 for <code>llar.forecast</code>

Details

`llar` does the Casdagli test of non-linearity. Given the embedding state-space (of dimension `m` and time delay `d`) obtained from time series `series`, for a sequence of distance values `eps`, the relative error made by forecasting time series values with a linear autoregressive model estimated on points closer than `eps` is computed. If minimum error is reached at relatively small length scales, a global linear model may be inappropriate (using current embedding parameters). This was suggested by Casdagli(1991) as a test for non-linearity.

`llar.predict` tries to extend the given time series by `n.ahead` points by iteratively fitting locally (in the embedding space of dimension `m` and time delay `d`) a linear model. If the spatial neighbourhood window is too small, your time series last point would be probably isolated. You can ask to automatically enlarge the window `eps` by a factor of `r%` sequentially, until enough neighbours are found for fitting the linear model.

`llar.fitted` gives out-of-sample fitted values from locally linear models.

Value

`llar` gives an object of class 'llar'. I.e., a list of components:

<code>RMSE</code>	vector of relative errors
<code>eps</code>	vector of neighbourhood sizes (in the same order of <code>RMSE</code>)
<code>frac</code>	vector of fractions of the time series used for <code>RMSE</code> computation
<code>avfound</code>	vector of average number of neighbours for each point in the time series which can be plotted using the <code>plot</code> method, and transformed to a regular <code>data.frame</code> with the <code>as.data.frame</code> function.

Function `llar.forecast` gives the vector of `n` steps ahead locally linear iterated forecasts.

Function `llar.fitted` gives out-of-sample fitted values from locally linear models.

Warning

For long time series, this can be slow, especially for relatively big neighbourhood sizes.

Note

The C implementation was re-adapted from that in the TISEAN package ("ll-ar" routine, see references). However, here the euclidean norm is used, in place of the max-norm.

Author(s)

Antonio, Fabio Di Narzo

References

M. Casdagli, Chaos and deterministic versus stochastic nonlinear modelling, J. Roy. Stat. Soc. 54, 303 (1991)

Hegger, R., Kantz, H., Schreiber, T., Practical implementation of nonlinear time series methods: The TISEAN package; CHAOS 9, 413-435 (1999)

Examples

```
res <- llar(log(lynx), m=3, neps=7)
plot(res)
```

```
x.new <- llar.predict(log(lynx), n.ahead=20, m=3, eps=1, onvoid="enlarge", r=5)
lag.plot(x.new, labels=FALSE)
```

```
x.fitted <- llar.fitted(log(lynx), m=3, eps=1)
lag.plot(x.fitted, labels=FALSE)
```

logLik.nlVar

Extract Log-Likelihood

Description

Log-Likelihood method for VAR models.

Usage

```
## S3 method for class 'nlVar'
logLik(object, ...)
```

Arguments

object object of class VAR computed by [lineVar](#).
... additional arguments to logLik.

Details

The Log-Likelihood is computed as in Luetkepohl (2006) equ. 3.4.5 (p. 89) and Juselius (2006) p. 56:

$$LL = -(TK/2) \log(2\pi) - (T/2) \log |\Sigma| - (1/2) \sum^T \left[(y_t - A' x_t)' \Sigma^{-1} (y_t - A' x_t) \right]$$

Where Σ is the Variance matrix of residuals, and x_t is the matrix stacking the regressors (lags and deterministic).

However, we use a computationally simpler version:

$$LL = -(TK/2) \log(2\pi) - (T/2) \log |\Sigma| - (TK/2)$$

See Juselius (2006), p. 57.

(Note that Hamilton (1994) 11.1.10, p. 293 gives $+(T/2) \log |\Sigma^{-1}|$, which is the same as $-(T/2) \log |\Sigma|$).

Value

Log-Likelihood value.

Author(s)

Matthieu Stigler

References

Hamilton (1994) *Time Series Analysis*, Princeton University Press

Juselius (2006) *The Cointegrated VAR model: methodology and Applications*, Oxford University Press

Luetkepohl (2006) *New Introduction to Multiple Time Series Analysis*, Springer

Examples

```
data(zeroyld)
data<-zeroyld

#Fit a VAR
VAR<-lineVar(data, lag=1)
logLik(VAR)
```

logLik.VECM	<i>Extract Log-Likelihood</i>
-------------	-------------------------------

Description

Log-Likelihood method for VECM models.

Usage

```
## S3 method for class 'VECM'
logLik(object, r, ...)
```

Arguments

object	object of class VECM computed by VECM .
r	The cointegrating rank. By default the rank specified in the call to VECM , but can be set differently by user.
...	additional arguments to logLik.

Details

The Log-Likelihood is computed in two different ways, depending on whether the VECM was estimated with ML (Johansen) or 2OLS (Engle and Granger).

When the model is estimated with ML, the LL is computed as in Hamilton (1994) 20.2.10 (p. 637):

$$LL = -(TK/2) \log(2\pi) - (TK/2) - (T/2) \log |\hat{\Sigma}_{UU}| - (T/2) \sum_{i=1}^r \log(1 - \hat{\lambda}_i)$$

Where Σ_{UU} is the variance matrix of residuals from the first auxiliary regression, i.e. regressing Δy_t on a constant and lags, $\Delta y_{t-1}, \dots, \Delta y_{t-p}$. λ_i are the eigenvalues from the $\Sigma_V^{-1} \Sigma_{VU} \Sigma_U^{-1} \Sigma_{UV}$, see 20.2.9 in Hamilton (1994).

When the model is estimated with 2OLS, the LL is computed as:

$$LL = \log |\Sigma|$$

Where Σ is the variance matrix of residuals from the the VECM model. There is hence no correspondence between the LL from the VECM computed with 2OLS or ML.

Value

Log-Likelihood value.

Author(s)

Matthieu Stigler

References

Hamilton (1994) *Time Series Analysis*, Princeton University Press

Examples

```
data(zeroyld)
data<-zeroyld

#Fit a VAR
vecm<-VECM(data, lag=1,r=1, estim="ML")
logLik(vecm)
```

LSTAR

Logistic Smooth Transition AutoRegressive model

Description

Logistic Smooth Transition AutoRegressive model.

Usage

```
lstar(x, m, d=1, steps=d, series, mL, mH, mTh, thDelay,
      thVar, th, gamma, trace=TRUE, include = c("const", "trend", "none", "both"),
      control=list(), starting.control=list())
```

Arguments

x	time series
m, d, steps	embedding dimension, time delay, forecasting steps
series	time series name (optional)
mL	autoregressive order for 'low' regime (default: m). Must be <=m
mH	autoregressive order for 'high' regime (default: m). Must be <=m
thDelay	'time delay' for the threshold variable (as multiple of embedding time delay d)
mTh	coefficients for the lagged time series, to obtain the threshold variable
thVar	external threshold variable
th, gamma	starting values for coefficients in the LSTAR model. If missing, a grid search is performed
trace	should additional infos be printed? (logical)
include	Type of deterministic regressors to include
control	further arguments to be passed as control list to optim
starting.control	further arguments for the grid search (dimension, bounds). See details below.

Details

$$x_{t+s} = (\phi_{1,0} + \phi_{1,1}x_t + \phi_{1,2}x_{t-d} + \dots + \phi_{1,mL}x_{t-(mL-1)d})G(z_t, th, \gamma) + (\phi_{2,0} + \phi_{2,1}x_t + \phi_{2,2}x_{t-d} + \dots + \phi_{2,mH}x_{t-(mH-1)d})$$

with z the threshold variable, and G the logistic function, computed as `plogis(q, location = th, scale = 1/gamma)`, so see [plogis](#) documentation for details on the logistic function formulation and parameters meanings. The threshold variable can alternatively be specified by:

$$\mathbf{mTh} \quad z[t] = x[t]mTh[1] + x[t-d]mTh[2] + \dots + x[t-(m-1)d]mTh[m]$$

$$\mathbf{thDelay} \quad z[t] = x[t - thDelay * d]$$

$$\mathbf{thVar} \quad z[t] = thVar[t]$$

Note that if starting values for `phi1` and `phi2` are provided, isn't necessary to specify `mL` and `mH`. Further, the user has to specify only one parameter between `mTh`, `thDelay` and `thVar` for indicating the threshold variable.

Estimation of the transition parameters `th` and `gamma`, as well as the regression parameters `phi1` and `phi2`, is done using concentrated least squares, as suggested in *Leybourne et al. (1996)*.

Given `th` and `gamma`, the model is linear, so regression coefficients can be obtained as usual by OLS. So the nonlinear numerical search needs only to be done for `th` and `gamma`; the regression parameters are then recovered by OLS again from the optimal `th` and `gamma`.

For the nonlinear estimation of the parameters `th` and `gamma`, the program uses the `optim` function, with optimization method BFGS using the analytical gradient. For the estimation of standard values, `optim` is re-run using the complete Least Squares objective function, and the standard errors are obtained by inverting the hessian. You can pass further arguments to `optim` directly with the control list argument. For instance, the option `maxit` maybe useful when there are convergence issues (see examples).

Starting parameters are obtained doing a simple two-dimensional grid-search over `th` and `gamma`. Parameters of the grid (interval for the values, dimension of the grid) can be passed to `starting.control`.

`nTh` The number of threshold values (`th`) in the grid. Defaults to 200

`nGamma` The number of smoothing values (`gamma`) in the grid. Defaults to 40

`trim` The minimal percentage of observations in each regime. Defaults to 10% (possible threshold values are between the 0.1 and 0.9 quantile)

`gammaInt` The lower and higher smoothing values of the grid. Defaults to `c(1,40)`

`thInt` The lower and higher threshold values of the grid. When not specified (default, i.e NA), the interval are the `trim` quantiles above.

Value

An object of class `nlar`, subclass `lstar`, i.e. a list with fitted model informations.

Author(s)

Antonio, Fabio Di Narzo

References

Non-linear time series models in empirical finance, Philip Hans Franses and Dick van Dijk, Cambridge: Cambridge University Press (2000).

Non-Linear Time Series: A Dynamical Systems Approach, Tong, H., Oxford: Oxford University Press (1990).

Leybourne, S., Newbold, P., Vougas, D. (1998) Unit roots and smooth transitions, Journal of Time Series Analysis, 19: 83-97

See Also

[plot.lstar](#) for details on plots produced for this model from the `plot` generic.

Examples

```
#fit a LSTAR model. Note 'maxit': slow convergence
mod.lstar <- lstar(log10(lynx), m=2, mTh=c(0,1), control=list(maxit=3000))
mod.lstar

#fit a LSTAR model without a constant in both regimes.
mod.lstar2 <- lstar(log10(lynx), m=1, include="none")
mod.lstar2

#Note in example below that the initial grid search seems to be too narrow.
# Extend it, and evaluate more values (slow!):
controls <- list(gammaInt=c(1,2000), nGamma=50)
mod.lstar3 <- lstar(log10(lynx), m=1, include="none", starting.control=controls)
mod.lstar3

# a few methods for lstar:
#summary(mod.lstar)
residuals(mod.lstar)
AIC(mod.lstar)
BIC(mod.lstar)
plot(mod.lstar)
predict(mod.lstar, n.ahead=5)
```

m.unrate

Monthly US unemployment

Description

Monthly US civilian unemployment rate from 1948 through 2004. Used in the book financial time series for Tsay (2005, chapter 4)

Usage

```
data(m.unrate)
```

Format

zoo object

Source

<http://faculty.chicagobooth.edu/ruey.tsay/teaching/fts2>

References

Ruey Tsay (2005) Analysis of Financial Time Series, 2nd ed. (Wiley, ch. 4)

MakeThSpec

Specification of the threshold search

Description

This optional function allows the user to set different restrictions for the threshold grid search in function `selectSETAR`.

Usage

```
MakeThSpec(ngrid = c("All", "Half", "Third", "Quarter"), exact = NULL,
           int = c("from", "to"), around = "val", ...)
```

Arguments

<code>ngrid</code>	The number of values to search for
<code>exact</code>	The user give an exact threshold value
<code>int</code>	The user gives an interval to search inside
<code>around</code>	The user gives an point to search around
<code>...</code>	currently unused

Details

This function is just to check the inputs for the specification of the grid search. If not provided, the search will be in the biggest interval (`ngrid = "All"`) between the minimum and maximum values. The user can reduce it by giving setting "Half" (only every two points is taken) and so on, or setting a number.

The search can also be made around a point, or between two points. When between a point, the argument `ngrid` is still used, whereas for `around`, a value of 30 is taken as default value if `ngrid` is not specified by user.

Value

The input values are given as output after checking for consistency (only one of `exact/int/around` should be given).

Author(s)

Matthieu Stigler

See Also[selectSETAR](#)**Examples**

```
sun<-(sqrt(sunspot.year+1)-1)*2
selectSETAR(sun, m=3, th=MakeThSpec(exact=10.40967),criterion="SSR", d=1, thDelay=0:2,
            plot=FALSE, nthresh=1)
#when pre-sepcified value does not correspond, function will search nearest value
selectSETAR(sun, m=3, th=MakeThSpec(exact=10.4),criterion="SSR", d=1, thDelay=0:2,
            plot=FALSE, nthresh=1)
#search around:
selectSETAR(sun, m=3, th=MakeThSpec(around=10.40967, ngrid=20),criterion="SSR", d=1, thDelay=0:2,
            plot=FALSE, nthresh=1)
#search in an interval
selectSETAR(sun, m=3, th=MakeThSpec(int=c(10, 11), ngrid=20),criterion="SSR", d=1, thDelay=0:2,
            plot=FALSE, nthresh=1)
#reduce size of the grid:
selectSETAR(sun, m=3, th=MakeThSpec(ngrid="Half"),criterion="SSR", d=1, thDelay=0:2,
            plot=FALSE, nthresh=1)

# 2 thresholds:
selectSETAR(sun, m=3, th=MakeThSpec(ngrid="Half"),criterion="SSR", d=1, thDelay=0:2,
            plot=FALSE, nthresh=2)
```

MAPE

Mean Absolute Percent Error

Description

Generic function to compute the Mean Absolute Percent Error of a fitted model.

Usage

```
MAPE(object, ...)
```

```
## Default S3 method:
```

```
MAPE(object, ...)
```

Arguments

object object of class `nlr.fit`
... additional arguments to MAPE

Value

Computed Mean Absolute Percent Error for the fitted model.

Author(s)

Antonio, Fabio Di Narzo

mse

Mean Square Error

Description

Generic function to compute the Mean Squared Error of a fitted model.

Usage

```
mse(object, ...)
```

```
## Default S3 method:  
mse(object, ...)
```

Arguments

object object of class `nlr.fit`
... additional arguments to mse

Value

Computed MSE for the fitted model.

Author(s)

Antonio, Fabio Di Narzo

nlar methods

nlar methods

Description

Generic ‘nlar’ methods. Method ‘nlar’ is described in a separate page: [predict.nlar](#)

Usage

```
## S3 method for class 'nlar'
AIC(object, k=2,...)
## S3 method for class 'nlar'
coef(object, ...)
## S3 method for class 'nlar'
fitted(object, ...)
## S3 method for class 'nlar'
MAPE(object, ...)
## S3 method for class 'nlar'
mse(object, ...)
## S3 method for class 'nlar'
print(x, digits = max(3, getOption("digits") - 3), ...)
## S3 method for class 'nlar'
residuals(object, ...)
## S3 method for class 'nlar'
summary(object, ...)
## S3 method for class 'nlar'
plot(x, ask=interactive(), ...)
## S3 method for class 'nlar'
toLatex(object, digits, label, ...)
```

Arguments

x, object	fitted ‘nlar’ object
ask	graphical option. See par
digits	For print method, see printCoefmat .
k	numeric, the penalty per parameter to be used; the default k = 2 is the classical AIC
label	LaTeX label passed to the equation
...	further arguments to be passed to and from other methods

Details

MAPE Mean Absolute Percent Error

mse Mean Square Error

plot Diagnostic plots

Author(s)

Antonio, Fabio Di Narzo

See Also

[availableModels](#) for listing all currently available models.

Examples

```
x <- log10(lynx)
mod.setar <- setar(x, m=2, thDelay=1, th=3.25)
mod.setar
AIC(mod.setar)
mse(mod.setar)
MAPE(mod.setar)
coef(mod.setar)
#summary(mod.setar)

e <- residuals(mod.setar)
e <- e[!is.na(e)]
plot(e)
acf(e)

plot(x)
lines(fitted(mod.setar), lty=2)
legend(x=1910, y=3.9, lty=c(1,2), legend=c("observed", "fitted"))

plot(mod.setar)
```

NNET

Neural Network nonlinear autoregressive model

Description

Neural Network nonlinear autoregressive model.

Usage

```
nnetTs(x, m, d = 1, steps = d, series, size,
control = list(trace = FALSE))
```

Arguments

x	time series
m, d, steps	embedding dimension, time delay, forecasting steps
series	time series name (optional)
size	number of hidden units in the neural network
control	control list to be passed to <code>nnet::nnet</code> optimizer

Details

Neural network model with 1 hidden layer and linear output:

$$x_{t+s} = \beta_0 + \sum_{j=1}^D \beta_j g(\gamma_{0j} + \sum_{i=1}^m \gamma_{ij} x_{t-(i-1)d})$$

Model is estimated using the `nnet` function in `nnet` package. Optimization is done via the BFGS method of `optim`. Note that for this model, no additional model-specific summary and plot methods are made available from this package.

Value

An object of class `nlar`, subclass `nnetTs`, i.e. a list with mostly `nnet : : nnet` internal structures.

Author(s)

Antonio, Fabio Di Narzo

References

Non-linear time series models in empirical finance, Philip Hans Franses and Dick van Dijk, Cambridge: Cambridge University Press (2000).

Non-Linear Time Series: A Dynamical Systems Approach, Tong, H., Oxford: Oxford University Press (1990).

Chaos: A Statistical Perspective, Chan, K., Tong, H., New York: Springer-Verlag (2001).

Examples

```
#fit a Neural Network model
mod.nnet <- nnetTs(log(lynx), m=2, size=3)
mod.nnet
```

plot methods

Plotting methods for SETAR and LSTAR subclasses

Description

Plotting methods 'setar' and 'lstar' subclasses

Usage

```
## S3 method for class 'setar'
plot(x, ask=interactive(), legend=FALSE, regSwStart, regSwStop, ...)
## S3 method for class 'lstar'
plot(x, ask=interactive(), legend=FALSE, regSwStart, regSwStop, ...)
```

Arguments

x	fitted 'setar' or 'lstar' object
ask	graphical option. See par
legend	Should a legend be plotted? (logical)
regSwStart, regSwStop	optional starting and stopping time indices for regime switching plot
...	further arguments to be passed to and from other methods

Details

These plot methods produce a plot which gives to you an idea of the behaviour of the fitted model.

Firstly, if embedding dimension is, say, m , m scatterplots are produced. On the x axis you have the lagged time series values. On the y axis the 'response' time series values. Observed points are represented with different colors-symbols depending on the level of the threshold variable. Specifically, for the setar model, black means 'low regime', red means 'high regime'. For the lstar model, where the self-threshold variable is continuous, threshold values are grouped in 5 different zones with the same number of points in each. Note that if more than 300 points are to be plotted, they all share the same symbol, and regimes can be distinguished only by color. If you want, by specifying `legend=TRUE` a legend is added at the upper-left corner of each scatterplot. To each scatterplot, a dashed line is superposed, which links subsequent fitted values.

Finally, a new time series plot is produced, with lines segments coloured depending on the regime (colors meanings are the same of those in the preceding scatterplots). Optionally, you can specify a starting and ending time indices, for zooming on a particular segment of the time series.

Author(s)

Antonio, Fabio Di Narzo

See Also

[setar](#), [lstar](#)

[nlar-methods](#) for other generic available methods for this kind of objects.

Examples

```
##  
##See 'setar' examples  
##
```

 predict.nlar

 Predict method for objects of class 'nlar'.

Description

Forecasting a non-linear model object of general class 'nlar', including 'setar' and 'star'.

Usage

```
## S3 method for class 'nlar'
predict(object, newdata, n.ahead = 1, type = c("naive", "MC",
  "bootstrap", "block-bootstrap"), nboot = 100, ci = 0.95, block.size = 3,
  boot1Zero = TRUE, ...)
```

Arguments

object	An object of class 'nlar'; generated by setar() or lstar().
newdata	Optional. A new data frame to predict from.
n.ahead	An integer specifying the number of forecast steps.
type	Type of forecasting method used. See details.
nboot	The number of replications for type MC or bootstrap.
ci	The forecast confidence interval (available only with types MC and bootstrap).
block.size	The block size when the block-bootstrap is used.
boot1Zero	Whether the first innovation for MC/bootstrap should be set to zero.
...	Further arguments passed to the internal 'oneStep' function. Mainly argument 'thVar' if an external threshold variable was provided

Details

The forecasts are obtained recursively from the estimated model. Given that the models are non-linear, ignoring the residuals in the 2- and more steps ahead forecasts leads to biased forecasts (so-called naive). Different resampling methods, averaging $n.boot$ times over future residuals, are available:

naive No residuals

MC Monte-Carlo method, where residuals are taken from a normal distribution, with $sd.$ equal to the residuals $sd.$

bootstrap Residuals are resampled from the empirical residuals from the model.

block-bootstrap Same as bootstrap, but residuals are resampled in block, with size $block.size$

The MC and bootstrap methods correspond to equations 3.90 and 3.91 of Franses and van Dijk (2000, p. 121). The bootstrap/MC is initiated either from the first forecast, $n.ahead=1$ (set with $boot1zero$ to TRUE), or from the second only.

When the forecast method is based on resampling, forecast intervals are available. These are obtained simply as empirical ci quantiles of the resampled forecasts (cf Method 2 in Franses and van Dijk, 2000, p. 122).

Value

A 'ts' object, or, in the case of MC/bootstrap, a list containing the prediction (pred) and the forecast standard errors (se).

Author(s)

Matthieu Stigler

References

Non-linear time series models in empirical finance, Philip Hans Franses and Dick van Dijk, Cambridge: Cambridge University Press (2000).

See Also

The model fitting functions [setar](#), [lstar](#).

A more sophisticated predict function, allowing to do sub-sample rolling predictions: [predict_rolling](#).

Examples

```
x.train <- window(log10(lynx), end = 1924)
x.test <- window(log10(lynx), start = 1925)

### Use different forecasting methods:
mod.set <- setar(x.train, m=2, thDelay=0)
pred_setar_naive <- predict(mod.set, n.ahead=10)
pred_setar_boot <- predict(mod.set, n.ahead=10, type="bootstrap", n.boot=200)
pred_setar_Bboot <- predict(mod.set, n.ahead=10, type="block-bootstrap", n.boot=200)
pred_setar_MC <- predict(mod.set, n.ahead=10, type="bootstrap", n.boot=200)

## Plot to compare results:
pred_range <- range(pred_setar_naive, pred_setar_boot$pred, pred_setar_MC$pred, na.rm=TRUE)
plot(x.test, ylim=pred_range, main="Comparison of forecasts methods from same SETAR")
lines(pred_setar_naive, lty=2, col=2)
lines(pred_setar_boot$pred, lty=3, col=3)
lines(pred_setar_Bboot$pred, lty=4, col=4)
lines(pred_setar_MC$pred, lty=5, col=5)

legLabels <- c("Observed", "Naive F", "Bootstrap F", "Block-Bootstrap F", "MC F")
legend("bottomleft", leg=legLabels, lty=1:5, col=1:5)
```

predict.TVAR *Predict method for objects of class 'VAR', 'VECM' or 'TVAR'*

Description

Forecasting the **level** of a series estimated by 'VAR' / 'VECM' or 'TVAR'

Usage

```
## S3 method for class 'TVAR'
predict(object, newdata, n.ahead = 5, newdataTrendStart, ...)

## S3 method for class 'VAR'
predict(object, newdata, n.ahead = 5, newdataTrendStart,
        exoPred = NULL, ...)
```

Arguments

object	An object of class 'VAR', 'VECM' or 'TVAR'
newdata	Optional. A new data frame to predict from. This should contain lags of the level of the original series. See Details.
n.ahead	An integer specifying the number of forecast steps.
newdataTrendStart	If 'newdata' is provided by the user, and the estimated model includes a trend, this argument specifies where the trend should start
...	Arguments passed to the unexported 'VAR.gen' or 'TVAR.gen' function
exoPred	vector/matrix of predictions for the exogenous variable(s) (with 'n.ahead' rows). Only for 'VAR'/'VECM', not for 'TVAR'.

Details

The forecasts are obtained recursively, and are for the levels of the series.

When providing newdata, newdata has to be ordered chronologically, so that the first row/element is the earliest value.

For VECM, the forecasts are obtained by transforming the VECM to a VAR (using function [VARrep](#)). Note that a VECM(lag=p) corresponds to a VAR(lag=p+1), so that if the user provides newdata for a VECM(lag=p), newdata should actually contain p+1 rows.

Value

A matrix of predicted values.

Author(s)

Matthieu Stigler

See Also

[lineVar](#) and [VECM.VARrep](#)

A more sophisticated predict function, allowing to do sub-sample rolling predictions: [predict_rolling](#).

Examples

```
data(barry)
barry_in <- head(barry, -5)
barry_out <- tail(barry, 5)

mod_vecm <- VECM(barry_in, lag=2)
mod_var <- lineVar(barry_in, lag=3)
mod_tvar <- TVAR(barry_in, lag=3, nthresh=1, thDelay=1)

pred_vecm <- predict(mod_vecm)
pred_var <- predict(mod_var)
pred_tvar <- predict(mod_tvar)

## compare forecasts on a plot
n <- 30
plot(1:n, tail(barry[,1], n), type="l", xlim=c(0,n))
lines((n-5+1):n, pred_var[,1], lty=2, col=2)
lines((n-5+1):n, pred_vecm[,1], lty=2, col=3)
lines((n-5+1):n, pred_tvar[,1], lty=2, col=4)
legend("bottomright", lty=c(1,2,2,2), col=1:4, legend=c("true", "var", "vecm", "tvar"))

## example for newdata:
all.equal(predict(mod_vecm), predict(mod_vecm, newdata=barry[c(317, 318, 319),]))
```

predict_rolling

Rolling forecasts

Description

Forecasts a VAR or VECM by discarding a part of the sample, and generating a series of updated forecasts.

Usage

```
predict_rolling(object, ...)

## S3 method for class 'nlVar'
predict_rolling(object, nroll = 10, n.ahead = 1,
  refit.every, newdata, ...)
```

Arguments

object	A linear object of class 'nlVar'; generated by lineVar or VECM .
...	Currently not used.
nroll	The number of rolling forecasts
n.ahead	An integer specifying the number of forecast steps.
refit.every	Determines every how many periods the model is re-estimated.
newdata	In case the model given is already estimated on the sub-sample, the out of sample data can be provided. Note it should contain observations to predict the first values, that are also contained in the in-sample.

Details

This function allows to check the out-of sample forecasting accuracy by estimating the model on a sub-sample of the original, then making `nroll` forecasts of horizon `n.ahead`, each time by updating the sample. In other words, with a given model estimated on 100 observations, the function will estimate it on say 90 first obs (`nroll=10`), generate a say 1 step-ahead `n.ahead=1` from obs 90, then using true value 91, 92,... till full sample.

Unlike usual `predict()` methods, specifying `n.ahead=2` will not generate a 1 step-ahead and a 2 step-ahead forecasts, but only `nroll` 2 step-ahead forecasts.

Note that while the forecasts are updated with new values, the model estimation is (by default) not updated. This can however be done with the argument `fit.every`, specifying at which frequency the model should be re-estimated. By setting it to 1 for example, each time a new observation is taken, the model is reestimated. This is similar to the [ugarchroll](#) in package **rugarch**.

Value

A matrix containing the forecasts.

Author(s)

Matthieu Stigler

See Also

[predict.nlar](#) for the standard predict function.

Examples

```
data(barry)

## model estimated on full sample:
mod_vec <- VECM(barry, lag=2)

## generate 10 1-step-ahead forecasts:
preds_roll <- predict_rolling(mod_vec, nroll=10)
```



```
## plot the results:
plot(window(barry[,"dolcan"],start=1998), type="l", ylab="barry: dolcan")
preds_roll_ts <- ts(preds_roll$pred, start=time(barry)[nrow(barry)-10], freq=12)
lines(preds_roll_ts[,"dolcan"], col=2, lty=2)
legend("bottomright", lty=c(1,2), col=1:2, leg=c("True", "Fitted"))
title("Comparison of true and rolling 1-ahead forecasts\n")
```

rank.select	<i>Selection of the cointegrating rank with Information criterion.</i>
-------------	--

Description

Selection of the cointegrating rank and the lags with Information criterion (AIC, BIC).

Usage

```
rank.select(data, lag.max = 10, r.max = ncol(data) - 1,
  include = c("const", "trend", "none", "both"), fitMeasure = c("SSR",
  "LL"), sameSample = TRUE, returnModels = FALSE)
```

```
## S3 method for class 'rank.select'
print(x, ...)
```

```
## S3 method for class 'rank.select'
summary(object, ...)
```

Arguments

data	multivariate time series.
lag.max	Maximum number of lags to investigate.
r.max	Maximum rank to investigate.
include	Type of deterministic regressors to include. See VECM or lineVar .
fitMeasure	Whether the AIC/BIC should be based on the full likelihood, or just the SSR. See explanations in logLik.VECM .
sameSample	Logical. Whether the data should be shortened so that the AIC/BIC are estimated on the same sample. Default to TRUE.
returnModels	Logical, default to FALSE. Whether the output should also contain the list of each model computed.
x	The output from rank.select for the print method.
...	Unused.
object	The output from rank.select for the summary method.

Details

This function estimates the AIC, BIC and Hannan-Quinn for each rank (up to `lags.max`) and lags (up to `lags.max`). This method has been shown to be useful to select simultaneously the rank and the lags, see references.

Value

An object of class 'rank.select', with 'print' and 'summary methods', containing among other the matrices of AIC/BIC/HQ, the Likelihood, and best ranks according to each criterion.

Author(s)

Matthieu Stigler

References

- Aznar A and Salvador M (2002). Selecting The Rank Of The Cointegration Space And The Form Of The Intercept Using An Information Criterion. *Econometric Theory*, *18*(04), pp. 926-947. <URL: http://ideas.repec.org/a/cup/etheor/v18y2002i04p926-947_18.html>.
- Cheng X and Phillips PCB (2009). Semiparametric cointegrating rank selection. *Econometrics Journal* , *12*(s1), pp. S83-S104. <URL: <http://ideas.repec.org/a/ect/emjnl/v12y2009is1ps83-s104.html>>.
- Gonzalo J and Pitarakis J (1998). Specification via model selection in vector error correction models. *Economics Letters*, *60*(3), pp. 321 - 328. ISSN 0165-1765, <URL: [http://dx.doi.org/DOI:10.1016/S0165-1765\(98\)00129-3](http://dx.doi.org/DOI:10.1016/S0165-1765(98)00129-3)>.
- Kapetanios G (2004). The Asymptotic Distribution Of The Cointegration Rank Estimator Under The Akaike Information Criterion. *Econometric Theory*, *20*(04), pp. 735-742. <URL: http://ideas.repec.org/a/cup/etheor/v20y2004i04p735-742_20.html>.
- Wang Z and Bessler DA (2005). A Monte Carlo Study On The Selection Of Cointegrating Rank Using Information Criteria. *Econometric Theory*, *21*(03), pp. 593-620. <URL: http://ideas.repec.org/a/cup/etheor/v21y2005i03p593-620_05.html>.

See Also

[VECM](#) for estimating a VECM. [rank.test](#) (or [ca.jo](#) in package **urca**) for the classical Johansen cointegration test.

Examples

```
data(barry)

#
rk_sel <- rank.select(barry)
rk_sel
#summary(rk_sel)
```

rank.test	<i>Test of the cointegrating rank</i>
-----------	---------------------------------------

Description

Maximum-likelihood test of the cointegrating rank.

Usage

```
rank.test(vecm, type = c("eigen", "trace"), r_null, cval = 0.05)

## S3 method for class 'rank.test'
print(x, ...)

## S3 method for class 'rank.test'
summary(object, digits = max(1, getOption("digits") - 3),
        ...)
```

Arguments

vecm	'VECM' object computed with the function VECM .
type	Type of test, either 'trace' or 'eigenvalue'. See details below.
r_null	Rank to test specifically.
cval	Critical value level for the automatic test.
x	The output from rank.test for the print method.
...	Unused.
object	The output from rank.test for the summary method.
digits	The number of digits to use in format.pval

Details

This function computes the two maximum-likelihood tests for the cointegration rank from Johansen (1996). Tests are:

trace Test the hypothesis of rank 'h' against rank 'K', i.e. against the alternative that the system is stationary.

eigenvalue Test the hypothesis of rank 'h' against rank 'h+1'.

The test works for five specifications of the deterministic terms as in Doornik et al (1998), to be specified in the previous call to [VECM](#):

H_{ql} Unrestricted constant and trend: use include="both"

H_l Unrestricted constant and restricted trend: use include="const" and LRinclude="trend"

H_{lc} Unrestricted constant and no trend: use include="const"

H_c Restricted constant and no trend: use LRinclude="const"

H_z No constant nor trend: use include="none"

Two testing procedures can be used:

Specific test By specifying a value for 'r_null'. The 'pval' value returned gives the specific p-value.

Automatic test If no value is specified for 'r_null', the function makes a simple automatic test: returns the rank (slot 'r') of the first test not rejected (level specified by arg 'cval') as recommended i.a. in Doornik et al (1998, p. 544).

A full table with both test statistics and their respective p-values is given in the summary method.

P-values are obtained from the gamma approximation from Doornik (1998, 1999). Small sample values adjusted for the sample size are also available in the summary method. Note that the 'effective sample size' for these values is different from output in gretl for example.

Value

An object of class 'rank.test', with 'print' and 'summary methods'.

Comparison with urca

While `ca.jo` in package **urca** and `rank.test` both implement Johansen tests, there are a few differences:

- `rank.test` gives p-values, while `ca.jo` gives only critical values.
- `rank.test` allows for five different specifications of deterministic terms (see above), `ca.jo` for only three.
- `ca.jo` allows for seasonal and exogenous regressors, which is not available in `rank.test`.
- The lag is specified differently: K from `ca.jo` corresponds to $\text{lag}+1$ in `rank.test`.

Author(s)

Matthieu Stigler

References

- Doornik, J. A. (1998) Approximations to the Asymptotic Distributions of Cointegration Tests, *Journal of Economic Surveys*, 12, 573-93
- Doornik, J. A. (1999) Erratum [Approximations to the Asymptotic Distribution of Cointegration Tests], *Journal of Economic Surveys*, 13, i
- Doornik, Hendry and Nielsen (1998) Inference in Cointegrating Models: UK M1 Revisited, *Journal of Economic Surveys*, 12, 533-72
- Johansen, S. (1996) Likelihood-based inference in cointegrated Vector Autoregressive Models, Oxford University Press

See Also

`VECM` for estimating a VECM. `rank.select` to estimate the rank based on information criteria.

`ca.jo` in package `urca` for another implementation of Johansen cointegration test (see section ‘Comparison with `urca`’ for more infos).

Examples

```
data(barry)

## estimate the VECM with Johansen!
ve <- VECM(barry, lag=1, estim="ML")

## specific test:
ve_test_spec <- rank.test(ve, r_null=1)
ve_test_spec_tr <- rank.test(ve, r_null=1, type="trace")

ve_test_spec
ve_test_spec_tr

## No specific test: automatic method
ve_test_unspec <- rank.test(ve)
ve_test_unspec_tr <- rank.test(ve, type="trace")

ve_test_unspec
ve_test_unspec_tr

## summary method: output will be same for all types/test procedure:
#summary(ve_test_unspec_tr)

## The function works for many specification of the VECM(), try:
rank.test(VECM(barry, lag=3, estim="ML"))
rank.test(VECM(barry, lag=3, include="both", estim="ML"))
rank.test(VECM(barry, lag=3, LRinclude="const", estim="ML"))

## Note that the tests are simple likelihood ratio, and hence can be obtained also manually:
-2*(logLik(ve, r=1)-logLik(ve, r=2)) # eigen test, 1 against 2
-2*(logLik(ve, r=1)-logLik(ve, r=3)) # eigen test, 1 against 3
```

regime

Extract variable showing regime

Description

This function allows to extract the indicator variable specifying the regime in which the process is at time t .

Usage

```
regime(object, initVal = TRUE, timeAttr = TRUE, ...)
```

Arguments

object	object of class setar or nlVar
initVal	Logical. Whether the NA initial values should be returned. Default to TRUE.
timeAttr	Logical. Whether the time attributes should be returned. Default to TRUE.
...	additional arguments to regime

Value

Time series of same attributes as input to setar.

Author(s)

Matthieu Stigler

Examples

```
set<-setar(lynx, m=3)
regime(set)
regime(set, time=FALSE, initVal=FALSE)

plot(regime(set))
```

resVar

Residual variance

Description

Extracts the global and regime-dependant variance of the residuals

Usage

```
resVar(x, adj=c("OLS", "ML"))
```

Arguments

x	setar object
adj	Degrees of freedom adjustment for the variance

Details

The degree of freedom adjustment in the formula for the variance is the number of parameters when adj="OLS" or zero when adj="ML".

Value

A vector containing:

Total	The residual variance of the full sample
L, (M), H	The residual variance of the lower (L), middle (if two thresholds) (M) and higher (H) regimes

Author(s)

Matthieu Stigler

References

Non-Linear Time Series: A Dynamical Systems Approach, Tong, H., Oxford: Oxford University Press (1990).

Examples

```
#Lynx model as in Tong (1980, p. 387)
mod.setar <- setar(log10(lynx), mL=7,mH=2, thDelay=1, th=3.116)
mod.setar
#summary(mod.setar)
#coefficients are same for lower regime but differ for higer

resVar(mod.setar, adj="ML")
#variance or the residuals is same for lower regime but differ for higer regime and hence for total

#Lynx model as in Tong (1980, p. 405)
mod.setar2 <- setar(log10(lynx), mL=1,mM=7,mH=2, thDelay=1, nthresh=2,th=c(2.373, 3.154))
round(coefficients(mod.setar2),3)

resVar(mod.setar2, adj="ML")
```

selectHyperParms *Automatic selection of model hyper-parameters*

Description

Automatic selection of model hyper-parameters

Usage

```
selectLSTAR(x, m, d=1, steps=d, mL = 1:m, mH = 1:m, thDelay=0:(m-1),
           fast=TRUE, trace=FALSE)
selectNNET(x, m, d=1, steps=d, size=1:(m+1), maxit=1e3, trace=FALSE)
```

Arguments

<code>x</code>	time series
<code>m, d, steps</code>	embedding parameters. For their meanings, see help about <code>nlar</code>
<code>mL, mH</code>	Vector of ‘low’ and ‘high’ regimes autoregressive orders
<code>thDelay</code>	Vector of ‘threshold delay’ values
<code>size</code>	Vector of numbers of hidden units in the nnet model
<code>maxit</code>	Max. number of iterations for each model estimation
<code>fast</code>	For LSTAR selection, whether a fast algorithm using starting values fro previous models should be used
<code>trace</code>	Logical. Whether informations from each model should be returned.

Details

Functions for automatic selection of LSTAR and NNET models hyper parameters. An exhaustive search over all possible combinations of values of specified hyper-parameters is performed. Embedding parameters `m, d, steps` are kept fixed.

Selection criterion is the usual AIC.

For the LSTAR model, two methods are offered:

fast=FALSE Each model is run separately, each time using the full grid search for starting values.

fast=TRUE Only the first model is run with a full grid search, while the subsequent use the first model results for their starting values.

Value

A data-frame, with columns giving hyper-parameter values and the computed AIC for each row (only the best 10s are returned)

Author(s)

Antonio, Fabio Di Narzo

Examples

```
llynx <- log10(lynx)
selectLSTAR(llynx, m=2)
selectNNET(llynx, m=3, size=1:5)
```

selectSETAR *Automatic selection of SETAR hyper-parameters*

Description

Automatic selection of SETAR hyper-parameters

Usage

```
selectSETAR(x, m, d=1, steps=d, series, mL, mH,mM, thDelay=0, mTh, thVar,
  th=MakeThSpec(), trace=TRUE, include = c("const", "trend","none", "both"),
  common=c("none", "include","lags", "both"), model=c("TAR", "MTAR"),
  ML=seq_len(mL), MH=seq_len(mH), MM=seq_len(mM), nthresh=1, trim=0.15,
  criterion = c("pooled-AIC", "AIC", "BIC", "SSR"),thSteps = 7, plot=TRUE,
  max.iter=2, type=c("level", "diff", "ADF"), same.lags=FALSE,
  restriction=c("none","OuterSymAll","OuterSymTh"), hpc=c("none", "foreach") )
```

Arguments

x	time series
m, d, steps	embedding parameters. For their meanings, see help about nlar
series	time series name (optional)
mL, mH,mM	autoregressive order for ‘low’ (mL) ‘middle’ (mM, only useful if nthresh=2) and ‘high’ (mH)regime (default values: m). Must be <=m. Alternatively, you can specify ML
thDelay	Vector of possible ‘threshold delay’ values to check for
mTh	coefficients for the lagged time series, to obtain the threshold variable
thVar	external threshold variable
th	Different specifications of the grid search, to pre-specify a value or set the number of points to search. See MakeThSpec
trace	should additional infos be printed? (logical)
include	Type of deterministic regressors to include
common	Indicates which elements are common to all regimes: no, only the include variables, the lags or both
model	Currently not implemented
ML,MM,MH	vector of lags for order for ‘low’ (ML) ‘middle’ (MM, only useful if nthresh=2) and ‘high’ (MH)regime. Max must be <=m
nthresh	Number of threshold of the model
trim	trimming parameter indicating the minimal percentage of observations in each regime. Default to 0.15
criterion	Model selection criterion
thSteps	Not used

plot	Should a plot showing the criterion values be printed? (logical)
max.iter	Number of iterations for the algorithm
type	Whether the variable is taken is level, difference or a mix (diff y= y-1, diff lags) as in the ADF test
same.lags	Logical. When AIC or pooled-AIC is used and arg m is given, should it search for same number of lags in each regime (TRUE) or allow for different (FALSE) lags in each regime. Different lags involves more computation
restriction	Restriction on the threshold. OuterSymAll will take a symmetric threshold and symmetric coefficients for outer regimes. OuterSymTh currently unavailable
hpc	Possibility to run the bootstrap on parallel core. See details

Details

Routine for automatic selection of SETAR models hyper parameters.

An exhaustive search over all possible combinations of values of specified hyper-parameters is performed. Thus the threshold delay, the number of lags in each regime and the threshold value are computed.

Embedding parameters d , steps are kept fixed.

Possible criteria are the usual SSR, AIC and a pooled AIC formula: $AIC(\text{lowregimemodel}) + AIC(\text{highregimemodel})$. The default criterion is the pooled AIC formula. SSR criterion can't be used to compare models with different lags.

When two thresholds($\text{nthresh}=2$) have to be computed, the search for the second is made conditional on results for first threshold as suggested in Gonzalo and Pittarakis (2002). Refinements can be obtained by using `max.iter` (first threshold being re-estimated based on the second one). If SSR is used, the number of lags in the inner regime is either the same if only `arg m` was given, otherwise it has to be pre-specified. Criterion AIC can be used to determine the number of lags in the inner regime, whereas pooled-aic is currently not implemented for $\text{nthresh}=2$.

By default, all threshold values excluding the upper and lower trim of the threshold values are taken as potential threshold. restriction can be made with `arg th`. See function `MakeThSpec`.

With the argument `hpc`, the heavy grid search can be run on parallel cores, thus alleviating the time of computation. Preliminary results indicate however that the length of the series must be very considerable in order that the parallel code becomes advantageous. To use it, the user needs simply to choose a package (among `doMC`, `doMPI`, `doSNOW` or `doRedis`) and register the backend. See the vignette for more details.

Value

An object of class `selectSETAR` (print and plot methods) with:

res	A data-frame, with columns giving hyper-parameter values and the computed AIC for each row (only the best 10/5s are returned)
res2	Same as res, returned if $\text{nthresh}=2$ otherwise set to NULL
bests	estimated hyper-parameters
th, firstBests, bests2th, ML, MM, MH	estimated parameters, from first and conditional search

```
criterion, nthresh, same.lags
                        returns args given by user
allTh                  all threshold values and corresponding criterion from first search
```

Author(s)

Antonio, Fabio Di Narzo and Stigler, Matthieu

References

Gonzalo, J. & Pitarakis, J. (2002) Estimation and model selection based inference in single and multiple threshold models, *Journal of Econometrics*, 110, 319 - 352

See Also

[selectLSTAR](#), [selectNNET](#), [MakeThSpec](#)

Examples

```
llynx <- log10(lynx)
selectSETAR(llynx, m=2)
#Suggested model is the following:
setar(llynx, m=2, thDelay=1, th=3.4)
```

SETAR

Self Threshold Autoregressive model

Description

Self Exciting Threshold AutoRegressive model.

Usage

```
setar(x, m, d=1, steps=d, series, mL, mM, mH, thDelay=0, mTh, thVar, th, trace=FALSE,
      nested=FALSE, include = c( "const", "trend", "none", "both"),
      common=c("none", "include", "lags", "both"), model=c("TAR", "MTAR"), ML=seq_len(mL),
      MM=seq_len(mM), MH=seq_len(mH), nthresh=1, trim=0.15, type=c("level", "diff", "ADF"),
      restriction=c("none", "OuterSymAll", "OuterSymTh") )
```

Arguments

x	time series
m, d, steps	embedding dimension, time delay, forecasting steps
series	time series name (optional)
mL, mM, mH	autoregressive order for 'low' (mL) 'middle' (mM, only useful if nthresh=2) and 'high' (mH) regime (default values: m). Must be <=m. Alternatively, you can specify ML

thDelay	'time delay' for the threshold variable (as multiple of embedding time delay d)
mTh	coefficients for the lagged time series, to obtain the threshold variable
thVar	external threshold variable
th	threshold value (if missing, a search over a reasonable grid is tried)
trace	should additional infos be printed? (logical)
include	Type of deterministic regressors to include
common	Indicates which elements are common to all regimes: no, only the include variables, the lags or both
ML, MM, MH	vector of lags for order for 'low' (ML) 'middle' (MM, only useful if nthresh=2) and 'high' (MH) regime. Max must be <=m
model	Currently not implemented
nthresh	Number of threshold of the model
trim	trimming parameter indicating the minimal percentage of observations in each regime. Default to 0.15
type	Whether the variable is taken is level, difference or a mix (diff y= y-1, diff lags) as in the ADF test
restriction	Restriction on the threshold. OuterSymAll will take a symmetric threshold and symmetric coefficients for outer regimes. OuterSymTh currently unavailable
nested	Whether is this a nested call? (useful for correcting final model df)

Details

Self Exciting Threshold AutoRegressive model.

$$X_{t+s} = x_{t+s} = (\phi_{1,0} + \phi_{1,1}x_t + \phi_{1,2}x_{t-d} + \dots + \phi_{1,mL}x_{t-(mL-1)d})I(z_t \leq th) + (\phi_{2,0} + \phi_{2,1}x_t + \phi_{2,2}x_{t-d} + \dots + \phi_{2,mH}x_{t-(mH-1)d})I(z_t > th)$$

with z the threshold variable. The threshold variable can alternatively be specified by (in that order):

thDelay $z[t] = x[t - thDelay*d]$

mTh $z[t] = x[t] mTh[1] + x[t-d] mTh[2] + \dots + x[t-(m-1)d] mTh[m]$

thVar $z[t] = thVar[t]$

For fixed th and threshold variable, the model is linear, so ϕ_1 and ϕ_2 estimation can be done directly by CLS (Conditional Least Squares). Standard errors for ϕ_1 and ϕ_2 coefficients provided by the summary method for this model are taken from the linear regression theory, and are to be considered asymptotical.

Value

An object of class `nlar`, subclass `setar`

Author(s)

Antonio, Fabio Di Narzo

References

Non-linear time series models in empirical finance, Philip Hans Franses and Dick van Dijk, Cambridge: Cambridge University Press (2000).

Non-Linear Time Series: A Dynamical Systems Approach, Tong, H., Oxford: Oxford University Press (1990).

See Also

[plot.setar](#) for details on plots produced for this model from the `plot` generic.

Examples

```
#fit a SETAR model, with threshold as suggested in Tong(1990, p 377)
mod.setar <- setar(log10(lynx), m=2, thDelay=1, th=3.25)
mod.setar
#summary(mod.setar)

## example in Tsay (2005)
data(m.unrate)
setar(diff(m.unrate), ML=c(2,3,4,12), MH=c(2,4,12), th=0.1, include="none")
```

setar.sim

Simulation and bootstrap of Threshold Autoregressive model

Description

Simulate or bootstrap a Threshold VAR

Usage

```
setar.sim(data, B, setarObject, n = 200, lag = 1, trend = TRUE,
  nthresh = 0, thDelay = 0, Thresh, type = c("boot", "simul", "check"),
  starting = NULL, rand.gen = rnorm, innov = rand.gen(n))
```

Arguments

<code>data</code>	univariate time series
<code>B</code>	vector of coefficients to simulate
<code>setarObject</code>	Object of class <code>linear</code> or <code>setar</code> to be bootstrapped
<code>n</code>	Number of observations to create when <code>type="simul"</code>
<code>lag</code>	Number of lags to include in each regime
<code>trend</code>	If a trend should be included in the model
<code>nthresh</code>	number of threshold (see details)
<code>thDelay</code>	'time delay' for the threshold variable (as multiple of embedding time delay <code>d</code>).
<code>Thresh</code>	The threshold value(s). Vector of length <code>nthresh</code>

type	Whether a bootstrap or simulation is to employ. See details
starting	Starting values when a simulation with given parameter matrix is made
rand.gen	optional: a function to generate the innovations.
innov	an optional times series of innovations. If not provided, rand.gen is used.

Details

This function offers the possibility to generate series following a TAR from two approaches: bootstrap or simulation. When the data is given, one can use a simple residual bootstrap or simulate a series from the parameter matrix and with normal distributed residuals (with variance pre-specified). The choice "check" is just there to check the function: one should obtain the same values as the given values. Please report if different. When the parameter matrix is given, there is only the possibility to simulate series. The starting values (of length equal to the number of lags) can be given. The user should take care for the choice of the starting values and parameters values, since it is not sure that the simulated values will cross the threshold even once.

Value

a list with the simulated/bootstrapped data and the parameter matrix used.

Author(s)

Matthieu Stigler

See Also

[SETAR](#) to estimate a SETAR, [arima.sim](#) to simulate an ARMA.

Examples

```
##Simulation of a TAR with 1 threshold
TvarMat <- c(2.9,-0.4,-0.1,-1.5, 0.2,0.3)
sim<-setar.sim(B=TvarMat,lag=2, type="simul", nthresh=1, Thresh=2, starting=c(2.8,2.2))$serie
mean(iffelse(sim>2,1,0)) #approximation of values over the threshold

#check the result
selectSETAR(sim, m=2)

##Bootstrap a TAR with two threshold (three regimes)
sun<-(sqrt(sunspot.year+1)-1)*2
setar.sim(data=sun,nthresh=2,n=500, type="boot", Thresh=c(6,9))$serie

##Check the bootstrap
cbind(setar.sim(data=sun,nthresh=2,n=500, type="check", Thresh=c(6,9))$serie,sun)
```

setarTest	<i>Test of linearity</i>
-----------	--------------------------

Description

Test of linearity against threshold of Hansen (1999) with bootstrap distribution

Usage

```
setarTest(x, m, d = 1, steps = d, series, thDelay = 0, nboot=10, trim=0.1,
          test=c("1vs", "2vs3"), hpc=c("none", "foreach"),check=FALSE)
```

Arguments

x	time series
m, d, steps	embedding dimension, time delay, forecasting steps
series	time series name (optional)
thDelay	'time delay' for the threshold variable (as multiple of embedding time delay d)
nboot	number of bootstrap replications
trim	trimming parameter indicating the minimal percentage of observations in each regime
test	Type of test. See details
hpc	Possibility to run the bootstrap on parallel core. See details in TVECM.HStest
check	Possibility to check if the bootstrap is correct by not sampling the residuals. The result given should be the same as in the original data

Details

Estimation of the first threshold parameter is made with CLS, a conditional search with one iteration is made for the second threshold. The Ftest comparing the residual sum of squares (SSR) of each model is computed.

$$F_{ij} = T((S_i - S_j)/S_j)$$

where S_i is the SSR of the model with i regimes (and so i-1 thresholds).

Three test are available. The both first can be seen as linearity test, whereas the third can be seen as a specification test: once the 1vs2 or/and 1vs3 rejected the linearity and henceforth accepted the presence of a threshold, is a model with one or two thresholds preferable?

Test **1vs2**: Linear AR versus 1 threshold TAR

Test **1vs3**: Linear AR versus 2 threshold2 TAR

Test **2vs3**: 1 threshold TAR versus 2 threshold2 TAR

The both first are computed together and available with test="1vs". The third test is available with test="2vs3".

The homoskedastic bootstrap distribution is based on resampling the residuals from H0 model (ar for test 1vs, and setar(1) for test 2vs3), estimating the threshold parameter and then computing the Fttest, so it involves many computations and is pretty slow.

Value

A object of class "Hansen99Test" containing:

SSRs	The residual Sum of squares of model AR, 1 threshold TAR and 2 thresholds TAR
Ftests	The Fttest statistic for the test
PvalBoot	The bootstrap p-values for the test selected
CriticalValBoot	The critical values for the test selected
Ftestboot	All the F-test computed
firstBests, secBests	The thresholds for the original series, obtained from search for 1 thresh (firstBests) and conditional search for 2 thresh (secBests)
nboot, m, type	The number of bootstrap replications (nboot), the lags used (m) and the type of test (type)

Author(s)

Matthieu Stigler

References

Hansen (1999) Testing for linearity, Journal of Economic Surveys, Volume 13, Number 5, December 1999 , pp. 551-576(26) available at: <http://www.ssc.wisc.edu/~bhansen/papers/cv.htm>

See Also

[TVAR.LRtest](#) for the multivariate version. [SETAR](#) for estimation of the model.

Examples

```
#Data used by Hansen
sun<-(sqrt(sunspot.year+1)-1)*2

#Test 1vs2 and 1vs3
#setarTest(sun, m=11, thDelay=0:1, nboot=5,trim=0.1, test="1vs")
```

sigmoid	<i>sigmoid functions</i>
---------	--------------------------

Description

Some sigmoid functions. See R sources for their definition

Usage

```
sigmoid(x)
dsigmoid(x)
```

Arguments

x numeric vector

Author(s)

J. L. Aznarte

STAR	<i>STAR model</i>
------	-------------------

Description

STAR model fitting with automatic selection of the number of regimes based on LM tests.

Usage

```
star(x, m=2, noRegimes, d = 1, steps = d, series, rob = FALSE,
     mTh, thDelay, thVar, sig=0.05, trace=TRUE, control=list(), ...)
```

Arguments

x	time series
m, d, steps	embedding dimension, time delay, forecasting steps
noRegimes	max number of regimes
series	time series name (optional)
rob	perform robust test (not implemented)
thDelay	'time delay' for the threshold variable (as multiple of embedding time delay d)
mTh	coefficients for the lagged time series, to obtain the threshold variable
thVar	external threshold variable

sig	significance level for the tests to select the number of regimes.
control	further arguments to be passed as control list to optim
trace	should additional infos be printed out?
...	currently unused

Details

The function `star` implements the iterative building strategy described in [1] to identify and estimate Smooth Transition AutoRegressive models.

[1] T. Terasvirta, "Specification, estimation and evaluation of smooth transition autoregressive models", J. Am. Stat. Assoc. 89 (1994): 208-218.

Value

`star` returns an object of class `nlar`, subclass `star`, i.e. a list with informations about the fitted model.

Author(s)

J. L. Aznarte M.

See Also

[addRegime](#)

Examples

```
mod.star <- star(log10(lynx), mTh=c(0,1), control=list(maxit=3000))
mod.star

addRegime(mod.star)
```

toLatex.setar

Latex representation of fitted setar models

Description

Produce LaTeX output of the SETAR model.

Usage

```
## S3 method for class 'setar'
toLatex(object, digits = 3, label, ...)
```

Arguments

object	fitted setar model (using nlar)
digits	options to be passed to format for formatting numbers
label	LaTeX label passed to the equation
...	Not used

Author(s)

Antonio, Fabio Di Narzo

See Also

[setar](#), [nlar-methods](#)

Examples

```
mod.setar <- setar(log10(lynx), m=2, thDelay=1, th=3.25)
toLatex(mod.setar)
```

TVAR

Multivariate Threshold Autoregressive model

Description

Estimate a multivariate Threshold VAR

Usage

```
TVAR(data, lag, include = c("const", "trend", "none", "both"),
      model = c("TAR", "MTAR"), commonInter = FALSE, nthresh = 1,
      thDelay = 1, mTh = 1, thVar, trim = 0.1, ngrid, gamma = NULL, around,
      plot = FALSE, dummyToBothRegimes = TRUE, trace = TRUE, trick = "for",
      max.iter = 2)
```

Arguments

data	time series
lag	Number of lags to include in each regime
include	Type of deterministic regressors to include
model	Whether the transition variable is taken in levels (TAR) or difference (MTAR)
commonInter	Whether the deterministic regressors are regime specific (commonInter=FALSE) or not.
nthresh	Number of thresholds

thDelay	'time delay' for the threshold variable (as multiple of embedding time delay d) PLEASE NOTE that the notation is currently different to univariate models in tsDyn. The left side variable is taken at time t, and not t+1 as in univariate cases.
mTh	combination of variables with same lag order for the transition variable. Either a single value (indicating which variable to take) or a combination
thVar	external transition variable
trim	trimming parameter indicating the minimal percentage of observations in each regime
ngrid	number of elements of the grid, especially for nthresh=3
gamma	prespecified threshold values
around	The grid search is restricted to <i>ngrid</i> values around this point. Especially useful for nthresh=3.
plot	Whether a plot showing the results of the grid search should be printed
dummyToBothRegimes	Whether the dummy in the one threshold model is applied to each regime or not.
trace	should additional infos be printed out?
trick	type of R function called: for or mapply
max.iter	Number of iterations for the algorithm

Details

For fixed th and threshold variable, the model is linear, so estimation can be done directly by CLS (Conditional Least Squares). The search of the parameters values is made upon a grid of potential values. So it is pretty slow.

nthresh=1: estimation of one threshold model (two regimes) upon a grid of *ngrid* values (default to ALL) possible thresholds and delays values.

nthresh=2: estimation of two thresholds model (three regimes) Conditional on the threshold found in model where nthresh=1, the second threshold is searched. When both are found, a second grid search is made with 30 values around each threshold.

nthresh=3: DOES NOT estimate a 3 thresholds model, but a 2 thresholds model with a whole grid over the thresholds parameters (so is really slow) with a given delay, is there rather to check the consistency of the method nthresh=2

Value

An object of class TVAR, with standard methods.

Author(s)

Matthieu Stigler

References

Lo and Zivot (2001) "Threshold Cointegration and Nonlinear Adjustment to the Law of One Price," *Macroeconomic Dynamics*, Cambridge University Press, vol. 5(4), pages 533-76, September.

See Also

[lineVar](#) for the linear VAR/VECM, [TVAR.LRtest](#) to test for TVAR, [TVAR.sim](#) to simulate/bootstrap a TVAR.

Examples

```
data(zeroyld)

tv <- TVAR(zeroyld, lag=2, nthresh=1, thDelay=1, trim=0.1, mTh=1, plot=FALSE)

print(tv)

# a few useful methods:
plot(tv)
predict(tv)
c(AIC(tv), BIC(tv), logLik(tv))
```

TVAR.LRtest	<i>Test of linearity</i>
-------------	--------------------------

Description

Multivariate extension of the linearity against threshold test from Hansen (1999) with bootstrap distribution

Usage

```
TVAR.LRtest(data, lag = 1, trend = TRUE, series, thDelay = 1:m, mTh = 1,
  thVar, nboot = 10, plot = FALSE, trim = 0.1, test = c("1vs", "2vs3"),
  model = c("TAR", "MTAR"), hpc = c("none", "foreach"), trace = FALSE,
  check = FALSE)
```

Arguments

data	multivariate time series
lag	Number of lags to include in each regime
trend	whether a trend should be added
series	name of the series
thDelay	'time delay' for the threshold variable (as multiple of embedding time delay d) PLEASE NOTE that the notation is currently different to univariate models in tsDyn. The left side variable is taken at time t, and not t+1 as in univariate cases.
mTh	combination of variables with same lag order for the transition variable. Either a single value (indicating which variable to take) or a combination
thVar	external transition variable
nboot	Number of bootstrap replications

plot	Whether a plot showing the results of the grid search should be printed
trim	trimming parameter indicating the minimal percentage of observations in each regime
test	Type of usual and alternative hypothesis. See details
model	Whether the threshold variable is taken in level (TAR) or difference (MTAR)
hpc	Possibility to run the bootstrap on parallel core. See details in TVECM.HStest
trace	should additional infos be printed? (logical)
check	Possibility to check the function by no sampling: the test value should be the same as in the original data

Details

This test is just the multivariate extension proposed by Lo and Zivot of the linearity test of Hansen (1999). As in univariate case, estimation of the first threshold parameter is made with CLS, for the second threshold a conditional search with one iteration is made. Instead of a Ftest comparing the SSR for the univariate case, a Likelihood Ratio (LR) test comparing the covariance matrix of each model is computed.

$$LR_{ij} = T(\ln(\det \hat{\Sigma}_i) - \ln(\det \hat{\Sigma}_j))$$

where $\hat{\Sigma}_i$ is the estimated covariance matrix of the model with i regimes (and so i-1 thresholds).

Three test are available. The both first can be seen as linearity test, whereas the third can be seen as a specification test: once the 1vs2 or/and 1vs3 rejected the linearity and henceforth accepted the presence of a threshold, is a model with one or two thresholds preferable?

Test **1vs2**: Linear VAR versus 1 threshold TVAR

Test **1vs3**: Linear VAR versus 2 threshold2 TVAR

Test **2vs3**: 1 threshold TAR versus 2 threshold2 TAR

The both first are computed together and available with test="1vs". The third test is available with test="2vs3".

The homoskedastik bootstrap distribution is based on resampling the residuals from H0 model, estimating the threshold parameter and then computing the Ftest, so it involves many computations and is pretty slow.

Value

A list containing:

-The values of each LR test

-The bootstrap Pvalues and critical values for the test selected

Author(s)

Matthieu Stigler

References

- Hansen (1999) Testing for linearity, *Journal of Economic Surveys*, Volume 13, Number 5, December 1999, pp. 551-576(26) available at: <http://www.ssc.wisc.edu/~bhansen/papers/cv.htm>
- Lo and Zivot (2001) "Threshold Cointegration and Nonlinear Adjustment to the Law of One Price," *Macroeconomic Dynamics*, Cambridge University Press, vol. 5(4), pages 533-76, September.

See Also

[setarTest](#) for the univariate version. [OlsTVAR](#) for estimation of the model.

Examples

```
data(zeroyld)
data<-zeroyld

TVAR.LRtest(data, lag=2, mTh=1, thDelay=1:2, nboot=3, plot=FALSE, trim=0.1, test="1vs")
```

TVAR.sim

Simulation of a multivariate Threshold Autoregressive model (TVAR)

Description

Simulate a multivariate Threshold VAR (TVAR)

Usage

```
TVAR.sim(B, Thresh, nthresh = 1, n = 200, lag = 1, include = c("const",
  "trend", "none", "both"), thDelay = 1, mTh = 1, starting = NULL,
  innov = rmnorm(n, varcov = varcov), varcov = diag(1, nrow(B)),
  show.parMat = FALSE, ...)
```

```
TVAR.boot(TVARobject, innov, seed, boot.scheme = c("resample", "wild1",
  "wild2", "check"), ...)
```

Arguments

B	Matrix of coefficients to simulate
Thresh	The threshold value(s). Vector of length nthresh
nthresh	number of threshold (see details)
n	Number of observations to create when type="simul"
lag	Number of lags to include in each regime
include	Type of deterministic regressors to include. NOT WORKING PROPERLY CURRENTLY if not const

thDelay	'time delay' for the threshold variable (as multiple of embedding time delay d) PLEASE NOTE that the notation is currently different to univariate models in tsDyn. The left side variable is taken at time t, and not t+1 as in univariate cases.
mTh	combination of variables with same lag order for the transition variable. Either a single value (indicating which variable to take) or a combination
starting	Starting values (matrix of dimension lag x k). If not given, set to zero.
innov	Innovations used for simulation. Should be matrix of dim n x k. By default multivariate normal. For the bootstrap case TVAR.boot, residuals are resampled if argument is missing.
varcov	Variance-covariance matrix for the innovations. By default identity matrix.
show.parMat	Logical. Should the parameter matrix be shown? Useful to understand how to give right input
...	Further arguments passed to the underlying (un-exported) TVAR.gen function
TVARobject	Object of class TVAR generated by function TVAR
seed	Optional. Seed for the random resampling function.
boot.scheme	The bootstrap scheme.

Details

This function offers the possibility to generate series following a TVAR.

By giving a matrix of coefficients, one can only simulate a VAR (nthresh=0) or TVAR (nthresh=1 or 2). One can have a specification with constant (default), trend, both or none (see arg include). Order in parameters is include/lags (VECM) and include/lags/include/lags for TVECM, hence, a matrix for a TVECM with 3 regimes, a const and a 2 lags would have 2 lines and 2*(1+4) columns. The innovations can be given by the user (a matrix of dim n x k, here n does not include the starting values!), by default it uses a multivariate normal distribution, with covariance matrix specified by varcov. The starting values (of dim lags x k) can be given. The user should take care for their choice, since it is not sure that the simulated values will cross the threshold even once.

The matrix 'B' has to be in the form: constant, trend, lags, then repeated if many regimes. In case of uncertainty, using who.parMat=TRUE will print the matrix as interpreted by the function, helping the user to feed the right input.

For the bootstrap, the function resamples data from a given TVAR model generated by TVAR, returning the resampled data. A residual recursive bootstrap is used, where one uses either a simple resampling, or the Wild bootstrap, either with a normal distribution (wild1) or inverting the sign randomly (wild2)

Value

A matrix with the simulated/bootstrapped series.

Author(s)

Matthieu Stigler

See Also

[TVAR](#) to estimate the TVAR. Similar [TVECM.sim](#) and [TVECM.boot](#) for [TVECM](#), [VAR.sim](#) and [VAR.boot](#) for VAR models estimated with [lineVar](#).

Examples

```
## TVAR.sim: Simulation of a TVAR with 1 threshold
B <- rbind(c(0.11928245, 1.00880447, -0.009974585, -0.089316, 0.95425564, 0.02592617),
          c(0.25283578, 0.09182279, 0.914763741, -0.0530613, 0.02248586, 0.94309347))
colnames(B) <- paste(rep(c("Const", "Lag_1_var1", "Lag_1_var2"), 2), c("Low", "High"), sep="_")
sim <- TVAR.sim(B=B, nthresh=1, n=500, mTh=1, Thresh=5, starting=matrix(c(5.2, 5.5), nrow=1))

#estimate the new serie
TVAR(sim, lag=1, dummyToBothRegimes=TRUE)

## TVAR.boot: Bootstrap a TVAR with two threshold (three regimes)
data(zeroyld)
serie <- zeroyld
mod <- TVAR(data=serie, lag=1, nthresh=1)
TVAR.boot(mod)
```

TVECM

Threshold Vector Error Correction model (VECM)

Description

Estimate a Threshold Vector Error Correction model (VECM)

Usage

```
TVECM(data, lag = 1, nthresh = 1, trim = 0.05, ngridBeta = 50,
       ngridTh = 50, plot = TRUE, th1 = list(exact = NULL, int = c("from",
"to"), around = "val"), th2 = list(exact = NULL, int = c("from", "to"),
around = "val"), beta = list(exact = NULL, int = c("from", "to"), around =
c("val", "by")), restr = c("none", "equal", "signOp"), common = c("All",
"only_ECT"), include = c("const", "trend", "none", "both"),
dummyToBothRegimes = TRUE, beta0 = 0, methodMapply = FALSE,
trace = TRUE)
```

Arguments

data	time series
lag	Number of lags to include in each regime
nthresh	number of threshold (see details)
trim	trimming parameter indicating the minimal percentage of observations in each regime

<code>ngridBeta</code>	number of elements to search for the cointegrating value
<code>ngridTh</code>	number of elements to search for the threshold value
<code>plot</code>	Whether the grid with the SSR of each threshold should be plotted.
<code>th1</code>	different possibilities to pre-specify an exact value, an interval or a central point for the search of the threshold (or first threshold if <code>nthresh=2</code>)
<code>th2</code>	different possibilities to pre-specify an exact value or a central point for the search of the second threshold (used only if <code>nthresh=2</code>)
<code>beta</code>	different possibilities to pre-specify an exact value, an interval or a central point for the search of the cointegrating value
<code>restr</code>	Currently not available
<code>common</code>	Whether the regime-specific dynamics are only for the ECT or for the ECT and the lags
<code>include</code>	Type of deterministic regressors to include
<code>dummyToBothRegimes</code>	Whether the dummy in the one threshold model is applied to each regime or not.
<code>beta0</code>	Additional regressors to include in the cointegrating relation
<code>methodMapply</code>	only for programming. Is to make the choice between a for loop or mapply implementation
<code>trace</code>	should additional infos be printed? (logical)

Details

For fixed threshold and cointegrating vector, the model is linear, so estimation of the regression parameters can be done directly by CLS (Conditional Least Squares). The search of the threshold and cointegrating parameters values which minimize the residual sum of squares (SSR) is made on a grid of potential values. For specification of the grids, see below.

The function can estimate one as well as two thresholds:

nthresh=1: estimation of one threshold model (two regimes) upon a grid of `ngridTh` values (default to ALL) possible thresholds and delays values.

nthresh=2: estimation of two thresholds model (three regimes). Conditional on the threshold found in model where `nthresh=1`, the second threshold is searched. When both are found, a second grid search is made with 30 values around each threshold.

The model can be either with a threshold effect on all variables ("All") or only on the error correction term (ECT) (argument "only ECT"). In the second case, the value for the middle threshold is taken a null, as in Balke and Fomby (1997).

The grid for the threshold parameters can be set in different ways, through the argument `th1`, `th2` and `beta`:

exact: Pre-specified value (for beta: cointegrating vector will be $c(1, -\beta)$)

int: Specify an interval (of length `ngridTh`) in which to search.

around: Specify to take `ngridTh` points around the value given.

The default is to do an interval search. Interval bounds for the threshold interval are simply the *trim* and *1-trim* percents of the sorted error correction term. For the cointegrating parameter, bounds of the interval are obtained from the (OLS) confidence interval of the linear cointegration case. It is often found however that this interval is too tight. It is hence recommended to inspect the plot of the grid search.

Value

Fitted model data

Author(s)

Matthieu Stigler

References

Hansen, B. and Seo, B. (2002), Testing for two-regime threshold cointegration in vector error-correction models, *Journal of Econometrics*, 110, pages 293 - 318

Seo, M. H. (2009) Estimation of non linear error-correction models, Working paper

See Also

[VECM](#) for the linear VECM, [TVAR](#) for the threshold VAR, [TVECM.SeoTest](#) to test for TVECM, [TVECM.sim](#) to simulate/bootstrap a TVECM.

Examples

```
data(zeroyld)

##Estimate a TVECM (we use here minimal grid, it should be usually much bigger!)

tvec <- TVECM(zeroyld, nthresh=2, lag=1, ngridBeta=20, ngridTh=30, plot=TRUE, trim=0.05, common="All")

#print(tvec)
#summary(tvec)

#Obtain diverse infos:
AIC(tvec)
BIC(tvec)

res.tvec<-residuals(tvec)

#export the equations as Latex:
#toLatex(tvec)
```

TVECM.HStest

Test of linear cointegration vs threshold cointegration

Description

Tests the null of linear cointegration against threshold cointegration following Hansen and Seo (2002). Fixed regressor and residual bootstrap are available.

Usage

```
TVECM.HStest(data, lag=1, ngridTh=300, trim=0.05,
  nboot=100, fixed.beta=NULL, intercept=TRUE,
  boot.type=c("FixedReg", "ResBoot"),
  hpc=c("none", "foreach"))
```

Arguments

data	Time series
lag	Number of lags to include in each regime
ngridTh	Number of threshold grid points to evaluate the optimal threshold.
trim	Trimming parameter indicating the minimal percentage of observations in each regime
nboot	Number of bootstrap replications
fixed.beta	Numeric. User pre-specified cointegrating value, as in VECM (i.e. cointegrating vector will be $c(1, -\text{fixed})$). When NULL (default), the value is estimated from the linear VECM.
intercept	Logical. Whether an intercept has to be included in the VECM
boot.type	Character. Type of bootstrap simulation (only if $nboot > 0$)
hpc	Possibility to run the bootstrap on parallel core. See details

Details

This test follows the implementation done by Hansen and Seo (2002). The cointegrating value is estimated from the linear VECM. Then, conditional on this value, the LM test is run for a range of different threshold values. The maximum of those LM test values is reported.

Two bootstrap are available: a fixed regressor, as well as a usual residual bootstrap (using the function [TVECM.sim](#)).

Available methods are `print()`, `summary()` and `plot()`.

With the argument `hpc`, the burdensome bootstrap replication can be run on parallel cores, thus alleviating the time of computation. The user needs simply to choose a package (among `doMC`, `doMPI`, `doSNOW` or `doRedis`) and register the backend. See the vignette for more details.

Value

A list containing diverse values:

stat	The sup-LM statistic.
values	The whole LM values.
PvalBoot	The bootstrap p-value
CriticalValBoot	The bootstrap critical values
allBoots	The boot sup-LM values
args	Some user given args (nboot, boot.type)

Reproducibility

Comparison with original paper is made difficult as values of the test are not shown in the paper, only their critical values, which depend on random bootstrap.

Comparison is done with the GAUSS code available on the page of Bruce Hansen. Running tar_ci, we have the same sup-LM value when lags=1 and lags=2, a higher value with lag=3. When the test is run with pre-specified beta values, we have different results, sometimes higher but also smaller sup-LM value.

Author(s)

Matthieu Stigler

References

Hansen, B. and Seo, B. (2002), Testing for two-regime threshold cointegration in vector error-correction models, *Journal of Econometrics*, 110, pages 293 - 318

See Also

[zeroyld](#): data used in the original paper of Hansen and Seo.

[TVECM.SeoTest](#): a similar test, but with null hypothesis of no-cointegration.

[TVECM](#) for estimating a TVECM, [TVECM.sim](#) for simulating/bootstrap a TVECM,

Examples

```
#Use original data from paper:
data(zeroyld)
dataPaper<-zeroyld
# Test: nboot, number of bootstrap replications, should be high
## Not run:
test1<-TVECM.HStest(dataPaper, lag=1, intercept=TRUE, nboot=1000)

## End(Not run)

#we use here for the example a much smaller number of bootstrap:
test1<-TVECM.HStest(dataPaper, lag=1, intercept=TRUE, nboot=10)
```

```

#test1
#summary(test1)
plot(test1)

#can have only specific plots:
plot(test1, which="LM values")
plot(test1, which="Density")

## Run the function in parallel:
## Not run:
#we show here the use with package doMC
library(doMC)
registerDoMC(2) #Number of cores
test1<-TVECM.HStest(dataPaper, lag=1, intercept=TRUE, nboot=1000, hpc="foreach")

## End(Not run)

```

TVECM.SeoTest

No cointegration vs threshold cointegration test

Description

Test the null of no cointegration against threshold cointegration with bootstrap distribution of Seo (2006)

Usage

```
TVECM.SeoTest(data, lag, beta, trim = 0.1, nboot, plot = FALSE,
  hpc = c("none", "foreach"), check = FALSE)
```

Arguments

data	time series
lag	Number of lags to include in each regime
beta	Pre-specified cointegrating value (i.e. cointegrating vector will be $c(1, -\beta)$)
trim	trimming parameter indicating the minimal percentage of observations in each regime
nboot	Number of bootstrap replications
plot	Whether a grid with the SSR of each threshold should be printed
hpc	Possibility to run the bootstrap on parallel core. See details in TVECM.HStest
check	Possibility to check the function by no sampling: the test value should be the same as in the original data

Details

For this test, the cointegrating value has to be specified by the user.

The model used is one where the threshold effect concerns only the cointegrating vector, and only in the outer regimes.

Due to the presence of parameters unidentified under the null hypothesis, the test employed is a Sup-Wald test, that means that for each combination of the thresholds, a Wald Test is computed and the supremum of all tests is taken. For each bootstrap replication, this approach is taken, so that the test is really slow.

Value

A list containing diverse informations:

Estimated threshold parameters and usual slope parameters.

Value of the test.

Critical and Pvalue from bootstrap distribution.

Author(s)

Matthieu Stigler

References

Seo, Myunghwan, 2006. "Bootstrap testing for the null of no cointegration in a threshold vector error correction model," *Journal of Econometrics*, vol. 127(1), pages 129-150, September.

See Also

[TVECM](#) for estimating a TVECM, [TVECM.sim](#) for simulating/bootstrap a TVECM,

Examples

```
# As the function takes long long time to be executed, we show in in don't run environment
## Not run:
data(zeroyld)

#can be useful to check whether the bootstrap is working:
#without sampling, results of boot should be same as original
#this is indeed not always the case duye to floating point algorithm
TVECM.SeoTest(zeroyld,lag=2, beta=1, trim=0.1,nboot=2, plot=FALSE,check=TRUE)

#then run the function:
TVECM.SeoTest(zeroyld,lag=2, beta=1, trim=0.1,nboot=100, plot=FALSE,check=FALSE)

## End(Not run)
```

UsUnemp	<i>US unemployment series used in Caner and Hansen (2001)</i>
---------	---

Description

This data, used as example in *Caner and Hansen (2001)*, contains the monthly US adult male unemployment from 1956 to 1999.

Usage

```
data(UsUnemp)
```

Format

A monthly time series of class `ts` starting in January 1956 and ending in August 1999.

Source

Caner and Hansen, Threshold autoregression with a unit root *Econometrica*, 2001, 69, 1555-1596
available at: <http://www.ssc.wisc.edu/~bhansen/papers/cv.htm>

VAR.sim	<i>Simulate or bootstrap a VAR model</i>
---------	--

Description

Allow to either simulate from scratch (by providing coefficients) or bootstrap from an estimated VAR model,

Usage

```
VAR.sim(B, n = 200, lag = 1, include = c("const", "trend", "none",
  "both"), starting = NULL, innov = rmnorm(n, varcov = varcov),
  varcov = diag(1, nrow(B)), show.parMat = FALSE, returnStarting = FALSE,
  ...)
```

```
VAR.boot(VARobject, boot.scheme = c("resample", "wild1", "wild2", "check"),
  seed, ...)
```


Arguments

B	Matrix of coefficients.
n	Number of observations to simulate
lag	Number of lags of the VAR to simulate
include	Type of deterministic regressors to include in the VAR to simulate
starting	Starting values (matrix of dimension lag x k) for the VAR to simulate. If not given, set to zero.
innov	Innovations used for in the VAR to simulate. Should be matrix of dim n x k. By default multivariate normal.
varcov	Variance-covariance matrix for the innovations. By default identity matrix.
show.parMat	Logical. Should the parameter matrix be shown? Useful to understand how to give right input
returnStarting	Whether starting values are returned. Default to FALSE
...	Further arguments passed to the underlying (un-exported) VAR.gen function
VARobject	Object of class VAR generated by function lineVar
boot.scheme	The bootstrap scheme. See details.
seed	Optional. Seed for the random resampling function.

Details

For the bootstrap, the function resamples data from a given VAR model generated by [lineVar](#), returning the resampled data. A residual recursive bootstrap is used, where one uses either a simple resampling, or the Wild bootstrap, either with a normal distribution (wild1) or inverting the sign randomly (wild2)

Value

A matrix with the resampled series.

Author(s)

Matthieu Stigler

See Also

[lineVar](#) to estimate the VAR. Similar [TVECM.sim](#) and [TVECM.boot](#) for [TVECM](#), [TVAR.sim](#) and [TVAR.boot](#) for [TVAR](#) models.

Examples

```
## VAR.sim: simulate VAR as in Enders 2004, p 268
B1<-matrix(c(0.7, 0.2, 0.2, 0.7), 2)
var1 <- VAR.sim(B=B1, n=100, include="none")
ts.plot(var1, type="l", col=c(1,2))
```

```

B2<-rbind(c(0.5, 0.5, 0.5), c(0, 0.5, 0.5))
varcov<-matrix(c(1,0.2, 0.3, 1),2)
var2 <- VAR.sim(B=B2, n=100, include="const", varcov=varcov)
ts.plot(var2, type="l", col=c(1,2))

## VAR.boot: Bootstrap a VAR
data(zeroyld)
mod <- lineVar(data=zeroyld,lag=1)
VAR.boot(mod)

```

VARrep

VAR representation

Description

Show the VAR representation of a VECM

Usage

```

VARrep(object, ...)

## S3 method for class 'VECM'
VARrep(object, ...)

## S3 method for class 'VAR'
VARrep(object, ...)

```

Arguments

object	An object of class ‘VECM’ created by VECM , or of class ‘VAR’ created by lineVar
...	Currently not used

Value

A matrix containing the parameters of the VECM under their VAR representation.

Author(s)

Matthieu Stigler

References

Hamilton (1994) *Time Series Analysis*, Princeton University Press

Examples

```

data(barry)

# VECM model:
mod_vecm <- VECM(barry, lag=2, estim="ML")
VARrep(mod_vecm)

# VAR model:
mod_var <- lineVar(barry, lag=2, I="diff")
VARrep(mod_var)

```

VECM

Estimation of Vector error correction model (VECM)

Description

Estimate a VECM by either Engle-Granger (2OLS) or Johansen (MLE) method.

Usage

```

VECM(data, lag, r = 1, include = c("const", "trend", "none", "both"),
      beta = NULL, estim = c("2OLS", "ML"), LRinclude = c("none", "const",
      "trend", "both"), exogen = NULL)

```

Arguments

data	multivariate time series (first row being first=oldest value)
lag	Number of lags (in the VECM representation, see Details)
r	Number of cointegrating relationships
include	Type of deterministic regressors to include
beta	for VECM only: user-specified cointegrating values, the cointegrating vector will be taken as: (1, -beta) If NULL, will be estimated using the estimator specified in estim
estim	Type of estimator: 2OLS for the two-step approach or ML for Johansen MLE
LRinclude	Type of deterministic regressors to include in the long-term relationship. Can also be a matrix with exogenous regressors (2OLS only).
exogen	Inclusion of exogenous variables (first row being first=oldest value). Is either of same size than data (then automatically cut) or than end-sample.

Details

This function is just a wrapper for the `lineVar`, with `model="VECM"`.

More comprehensive functions for VECM are in package `vars`. Differences with that package are:

Engle-Granger estimator The Engle-Granger estimator is available

Presentation Results are printed in a different ways, using a matrix form

lateX export The matrix of coefficients can be exported to latex, with or without standard-values and significance stars

Prediction The `predict` method contains a `newdata` argument allowing to compute rolling forecasts.

Two estimators are available: the Engle-Granger two step approach (2OLS) or the Johansen (ML). For the 2OLS, deterministic regressors (or external variables if `LRinclude` is of class `numeric`) can be added for the estimation of the cointegrating value and for the ECT. This is only working when the beta value is not pre-specified.

The arg `beta` is the cointegrating value, the cointegrating vector will be taken as: $(1, -\beta)$.

Note that the lag specification corresponds to the lags in the VECM representation, not in the VAR (as is done in package `vars` or software GRET). Basically, a VAR with 2 lags corresponds here to a VECM with 1 lag. The lag can be set to 0, although some methods (`irf`, `fevd`) won't work for this case.

#*The arg `beta` allows to specify constrained cointegrating values, leading to $ECT = \beta' X_{t-1}$. It should be specified as a $K \times r$ matrix. In case of $r = 1$, can also be specified as a vector. Note that the vector should be normalised, with the first value to 1, and the next values showing the opposite sign in the long-run relationship $-\beta$. In case the vector has $K - 1$ values, this is what `lineVar` is doing, setting $(1, -\beta)$. Note finally one should provide values for all the coefficients (eventually except for special case of $r=1$ and $k-1$), if you want to provide only part of the parameters, and let the others be estimated, look at the functions in package `urca`.

The eigenvector matrix β is normalised using the Phillips triangular representation, see Hamilton (1994, p. 576) and Juselius (2006, p. 216), see `coefA` for more details.

Value

An object of class `VECM` (and higher classes `VAR` and `n1Var`) with methods:

Usual methods `Print`, `summary`, `plot`, `residuals`, `fitted`, `vcov`

Fit criteria `AIC`, `BIC`, `MAPE`, `mse`, `logLik` (latter only for models estimated with MLE)

Prediction `Predict` and `predict_rolling`

VAR/VECM methods Impulse response function (`irf`) and forecast error variance decomposition (`fevd`)

LaTeX `toLatex`

Author(s)

Matthieu Stigler

References

- Hamilton (1994) Time Series Analysis, Princeton University Press
 Juselius (2006) The Cointegrated VAR model, Oxford University Press

See Also

[coefA](#), [coefB](#) and [coefPI](#) to extract the relevant parameter matrices.
[lineVar TVAR](#) and [TVECM](#) for the corresponding threshold models. [linear](#) for the univariate AR model.

Examples

```
data(zeroyld)
data<-zeroyld

#Fit a VECM with Engle-Granger 2OLS estimator:
vecm.eg<-VECM(zeroyld, lag=2)

#Fit a VECM with Johansen MLE estimator:
vecm.jo<-VECM(zeroyld, lag=2, estim="ML")

#compare results with package vars:
if(require(vars)) {
  data(finland)
  #check long coint values
  all.equal(VECM(finland, lag=2, estim="ML", r=2)$model.specific$beta,
            cajorls(ca.jo(finland, K=3, spec="transitory"), r=2) $beta, check.attributes=FALSE)
  # check OLS parameters
  all.equal(t(coefficients(VECM(finland, lag=2, estim="ML", r=2))),
            coefficients(cajorls(ca.jo(finland, K=3, spec="transitory"), r=2)$rlm), check.attributes=FALSE)
}

##export to Latex
#toLatex(vecm.eg)
#toLatex(summary(vecm.eg))
#options("show.signif.stars"=FALSE)
#toLatex(summary(vecm.eg), parenthese="Pvalue")
#options("show.signif.stars"=TRUE)
```

Description

Estimate or bootstraps a multivariate Threshold VAR

Usage

```
VECM.sim(data, B, VECMobject, beta, n = 200, lag = 1, type = c("simul",
  "boot", "check"), include = c("const", "trend", "none", "both"),
  starting = NULL, innov = rmnorm(n, varcov = varcov), varcov = diag(1,
  k), show.parMat = FALSE, seed)
```

```
VECM.boot(VECMobject, show.parMat = FALSE, seed, check = TRUE)
```

```
TVECM.boot(TVECMobject, show.parMat = FALSE, seed, check = TRUE)
```

```
TVECM.sim(data, B, TVECMobject, nthresh = 1, Thresh, beta, n = 200,
  lag = 1, type = c("simul", "boot", "check"), include = c("const",
  "trend", "none", "both"), starting = NULL, innov = rmnorm(n, varcov =
  varcov), varcov = diag(1, k), show.parMat = FALSE, seed)
```

Arguments

data	matrix of parameter to simulate
B	Matrix of coefficients to simulate
beta	The cointegrating value
n	Number of observations to create when type="simul"
lag	Number of lags to include in each regime
type	Whether a bootstrap or simulation is to employ. See details
include	Type of deterministic regressors to include. NOT WORKING PROPERLY CURRENTLY if not const
starting	Starting values when a simulation with given parameter matrix is made
innov	Innovations used for simulation. Should be matrix of dim nxk. By default multivariate normal.
varcov	Variance-covariance matrix for the innovations. By default multivariate normal is used.
show.parMat	Logical. Should the parameter matrix be shown? Useful to understand how to give right input
seed	Optional. Seed for the random number generation.
check	When performing a bootstrap replication, check if taking original residuals (instead of resampled) leads to the original data.
TVECMobject, VECMobject	Object computed by function TVECM or linear VECM
nthresh	number of threshold (see details)
Thresh	The threshold value(s). Vector of length nthresh

Details

This function offers the possibility to generate series following a VECM/TVECM from two approaches: bootstrap or simulation. `VECM.sim` is just a wrapper for `TVECM.sim`.

When the argument `matrix` is given, one can only simulate a VECM (`nthresh=0`) or TVECM (`nthresh=1` or `2`). One can have a specification with constant ("`const`"), "`trend`", "`both`" or "`none`" (see argument `include`). Order for the parameters is `ECT/include/lags` for VECM and `ECT1/include1/lags1/ECT2/include2/lags2` for TVECM. To be sure that once is using it correctly, setting `show.parMat = TRUE` will show the matrix of parameters together with their values and names.

The argument `beta` is the cointegrating value on the right side of the long-run relationship, and hence the function use the vector $(1, -\beta)$. The `innov` argument specifies the innovations. It should be given as a matrix of dim $n \times k$, (here n does not include the starting values!), by default it uses a multivariate normal distribution, with covariance matrix specified by `varcov`.

The starting values (of dim `lags` x `k`) can be given through argument `starting`. The user should take care for their choice, since it is not sure that the simulated values will cross the threshold even once. Notice that only one cointegrating value is allowed. User interested in simulating a VECM with more cointegrating values should do use the VAR representation and use `TVAR.sim`.

The second possibility is to bootstrap series. This is done on a object generated by `TVECM` (or `VECM`). A simple residual bootstrap is done, or one can simulate a series with the same parameter matrix and with normal distributed residuals (with variance pre-specified), corresponding to Monte-carlo simulations.

One can alternatively give only the series, and then the function will call internally `TVECM`.

Value

A matrix with the simulated/bootstraped series.

Author(s)

Matthieu Stigler

See Also

`VECM` or `TVECM` to estimate the VECM or TVECM. Similar `TVAR.sim` and `TVAR.boot` for `TVAR`, `VAR.sim` and `VAR.boot` for VAR models estimated with `lineVar` models.

Examples

```
###reproduce example in Enders (2004, 2 edition) p. 350,
# (similar example in Enders (2010, 3 edition) 301-302).

if(require(mnormt)){
#see that the full "VAR" coefficient matrix is:
  A <- matrix(c(-0.2, 0.2, 0.2, -0.2), byrow=TRUE, ncol=2)

# but this is not the input of VECM.sim. You should decompose into the a and b matrix:
```

```

a<-matrix(c(-0.2, 0.2), ncol=1)
b<-matrix(c(1,-1), nrow=1)

# so that:
a*%b

# The a matrix is the input under argument B, while the b matrix is under argument beta:
# (the other zeros in B are for the not-specified lags)
innov<-rmnorm(100, varcov=diag(2))
startVal <- matrix(0, nrow=2, ncol=1)
Bvecm <- rbind(c(-0.2, 0,0), c(0.2, 0,0))
vecm1 <- VECM.sim(B=Bvecm, beta=1,n=100, lag=1,include="none", innov=innov, starting=startVal)
ECT <- vecm1[,1]-vecm1[,2]

#add an intercept as in panel B
Bvecm2 <- rbind(c(-0.2, 0.1,0,0), c(0.2,0.4, 0,0))
vecm2 <- VECM.sim(B=Bvecm2, n=100,beta=1, lag=1,include="const", innov=innov, starting=startVal)

par(mfrow=c(2,1))
plot(vecm1[,1], type="l", main="Panel a: no drift or intercept", ylab="", xlab="")
lines(vecm1[,2], lty=2)
plot(vecm2[,1], type="l", main="Panel b: drift terms (0.1)", ylab="", xlab="")
lines(vecm2[,2], lty=2)
}
##Bootstrap a TVAR with 1 threshold (two regimes)
data(zeroyld)
dat<-zeroyld
TVECMobject<-TVECM(dat, nthresh=1, lag=1, ngridBeta=20, ngridTh=20, plot=FALSE)
TVECM.sim(TVECMobject=TVECMobject,type="boot")

##Check the bootstrap
TVECM.sim.check <- TVECM.sim(TVECMobject=TVECMobject,type="check")
#all(TVECM.sim.check==dat)

```

VECM_symbolic

Virtua VECM model

Description

Pedagogical tool to create a symbolic VECM model, i.e. just for representation purpose.

Usage

```
VECM_symbolic(alpha, beta, lags, inc, include = c("none", "const", "trend",
"both"))
```


Arguments

alpha	Matrix of alpha speed adjustment coefficients.
beta	Matrix of alpha, cointegrating coefficients.
lags	Matrix containing the lags coefficients.
inc	Matrix containing the include (see following arg) coefficients.
include	Character indicating the type of deterministic term included, if any.

Value

An object of class 'VECM', without however any data.

Examples

```
a<-matrix(c(-0.4, 0.1), ncol=1)
b<-matrix(c(1, -2), ncol=2)

# VECM_symb(alpha=a, beta=t(b))
d<- VECM_symbolic(alpha=a, beta=t(b))
VARrep(d)
d<- VECM_symbolic(alpha=a, beta=t(b), lags=matrix(0, ncol=2, nrow=2))
VARrep(d)
LagMat <- matrix(c(0.1, 0.3, 0.1, 0.2), ncol=2, nrow=2)
incMat <- matrix(c(0.5, 0.1), ncol=1)
d3<- VECM_symbolic(alpha=a, beta=t(b), lags=LagMat, inc=incMat, include="const")
VARrep(d3)
```

 zeroyld

zeroyld time series

Description

U.S. Term Structure Data, 1947-1991. Dataset used by Hansen and Seo (2002). The data contains the 12 month short rate and 120 month long rate.

Format

A data frame with 482 observations on 2 variables.

[,1]	short.run	numeric	Short term, 12 month
[,2]	long.run	numeric	Long term, 120 month

Source

Hansen, B. and Seo, B. (2002), Testing for two-regime threshold cointegration in vector error-correction models, *Journal of Econometrics*, 110, pages 293 - 318

The data can be downloaded from: http://www.ssc.wisc.edu/~bhansen/progs/joe_02r.zip.

The authors themselves took the data from the webpage of Huston McCulloch: <http://www.econ.ohio-state.edu/jhm/ts/mcckwon/mccull.htm>

See Also

[TVECM.HStest](#): Hansen and Seo test.

[TVECM](#) for estimating a TVECM.

Index

- *Topic **VAR**
 - VARrep, 82
- *Topic **VECM**
 - rank.select, 49
 - VARrep, 82
 - VECM_symbolic, 88
- *Topic **bootstrap**
 - TVAR.sim, 71
 - VAR.sim, 80
- *Topic **cointegration**
 - rank.select, 49
 - VARrep, 82
 - VECM_symbolic, 88
- *Topic **datasets**
 - barry, 10
 - IIPUs, 20
 - m.unrate, 36
 - UsUnemp, 80
 - zeroyld, 89
- *Topic **predict**
 - predict_rolling, 47
- *Topic **regression**
 - fevd, 17
 - fitted.nlVar, 18
 - irf, 21
 - predict.nlar, 44
 - predict.TVAR, 46
- *Topic **ts**
 - aar, 4
 - accuracy_stat, 5
 - addRegime, 6
 - autopairs, 7
 - autotriples, 8
 - autotriples.rgl, 9
 - availableModels, 10
 - delta, 14
 - delta.lin, 15
 - getTh, 19
 - isLinear, 23
 - lags.select, 25
 - LINEAR, 26
 - lineVar, 27
 - llar, 29
 - logLik.nlVar, 31
 - logLik.VECM, 33
 - LSTAR, 34
 - MAPE, 38
 - mse, 39
 - nlar methods, 40
 - NNET, 41
 - plot methods, 42
 - rank.select, 49
 - rank.test, 51
 - regime, 53
 - resVar, 54
 - selectHyperParms, 55
 - selectSETAR, 57
 - SETAR, 59
 - setar.sim, 61
 - setarTest, 63
 - sigmoid, 65
 - STAR, 65
 - toLatex.setar, 66
 - tsDyn-package, 3
 - TVAR, 67
 - TVAR.LRtest, 69
 - TVAR.sim, 71
 - TVECM, 73
 - TVECM.HStest, 76
 - TVECM.SeoTest, 78
 - VAR.sim, 80
 - VARrep, 82
 - VECM, 83
 - VECM.sim, 85
 - VECM_symbolic, 88
- AAR (aar), 4
- aar, 4
- accuracy, 5

- accuracy_stat, 5
- addRegime, 6, 66
- AIC.nlar (nlar methods), 40
- arma.sim, 62
- as.data.frame, 30
- as.data.frame.llar (llar), 29
- autopairs, 4, 7
- autotriples, 4, 8, 9
- autotriples.rgl, 4, 9
- availableModels, 4, 10, 41

- barry, 10
- BBCTest, 11, 17, 25
- bds.test, 15
- blrtest, 13

- ca.jo, 13, 50, 52, 53
- cajorls, 13
- coef.nlar (nlar methods), 40
- coefA, 84, 85
- coefA (coefB), 12
- coefB, 12, 85
- coefPI, 85
- coefPI (coefB), 12

- d2sigmoid (sigmoid), 65
- delta, 4, 14
- delta.lin, 4, 15
- delta.lin.test, 15
- dsigmoid (sigmoid), 65

- extendBoot, 16

- fevd, 17, 17, 84
- fitted (fitted.nlVar), 18
- fitted.nlar (nlar methods), 40
- fitted.nlVar, 18
- format, 67
- format.pval, 51

- gam, 4
- getTh, 19

- hnorm, 7, 8

- IIPUs, 20
- irf, 21, 22, 28, 84
- isLinear, 23
- KapShinTest, 24

- lags.select, 25
- LINEAR, 26
- linear, 28, 85
- linear (LINEAR), 26
- lineVar, 13, 18, 23, 27, 31, 47–49, 69, 73, 81, 82, 84, 85, 87
- llar, 4, 29
- logLik, 84
- logLik.nlVar, 31
- logLik.VECM, 25, 33, 49
- LSTAR, 34
- lstar, 43, 45
- lstar (LSTAR), 34

- m.unrate, 36
- MakeThSpec, 37, 57–59
- makeThSpec (MakeThSpec), 37
- MAPE, 38, 84
- MAPE.nlar (nlar methods), 40
- mse, 39, 84
- mse.nlar (nlar methods), 40

- nlar, 26, 27, 56, 57, 67
- nlar methods, 40
- nlar-methods, 43
- nlar-methods (nlar methods), 40
- NNET, 41
- nnet, 42
- nnetTs (NNET), 41

- OlsTVAR, 71
- OlsTVAR (TVAR), 67
- optim, 34, 35, 42, 66

- par, 40, 43
- plogis, 35
- plot, 18, 23
- plot methods, 42
- plot-methods (plot methods), 42
- plot.aar (aar), 4
- plot.llar (llar), 29
- plot.lstar, 36
- plot.lstar (plot methods), 42
- plot.nlar (nlar methods), 40
- plot.setar, 61
- plot.setar (plot methods), 42
- predict (predict.nlar), 44
- predict.nlar, 40, 44, 48
- predict.TVAR, 46

- predict.VAR, 28
- predict.VAR (predict.TVAR), 46
- predict.VECM (predict.TVAR), 46
- predict_rolling, 45, 47, 47, 84
- print.aar (aar), 4
- print.linear (LINEAR), 26
- print.llar (llar), 29
- print.nlar (nlar methods), 40
- print.rank.select (rank.select), 49
- print.rank.test (rank.test), 51
- print.summary.linear (LINEAR), 26
- print.varirf (irf), 21
- printCoefmat, 40

- rank.select, 25, 49, 53
- rank.test, 50, 51
- regime, 28, 53
- residuals.nlar (nlar methods), 40
- resVar, 54
- rgl, 9

- selectHyperParms, 55
- selectLSTAR, 59
- selectLSTAR (selectHyperParms), 55
- selectNNET, 59
- selectNNET (selectHyperParms), 55
- selectSETAR, 37, 38, 57
- selectSetar (selectSETAR), 57
- selectsetar (selectSETAR), 57
- SETAR, 59, 62, 64
- setar, 43, 45, 67
- setar (SETAR), 59
- setar.sim, 61
- setarTest, 12, 17, 25, 63, 71
- sigmoid, 65
- sm, 8
- sm.autoregression, 8
- sm.density, 7, 8
- sm.regression, 7, 8
- sm.ts.pdf, 8
- STAR, 65
- star, 7
- star (STAR), 65
- summary.aar (aar), 4
- summary.linear (LINEAR), 26
- summary.nlar (nlar methods), 40
- summary.rank.select (rank.select), 49
- summary.rank.test (rank.test), 51
- summary.setar (SETAR), 59

- terasvirta.test, 15
- toLatex, 28
- toLatex.nlar (nlar methods), 40
- toLatex.setar, 66
- tsDyn (tsDyn-package), 3
- tsDyn-package, 3
- TVAR, 28, 67, 72, 73, 75, 81, 85, 87
- TVAR.boot, 81, 87
- TVAR.boot (TVAR.sim), 71
- TVAR.LRtest, 64, 69, 69
- TVAR.sim, 69, 71, 81, 87
- TVECM, 28, 73, 73, 77, 79, 81, 85–87, 90
- TVECM.boot, 73, 81
- TVECM.boot (VECM.sim), 85
- TVECM.HStest, 63, 70, 76, 78, 90
- TVECM.HStest (TVECM.HStest), 76
- TVECM.SeoTest, 75, 77, 78
- TVECM.sim, 73, 75–77, 79, 81, 87
- TVECM.sim (VECM.sim), 85

- ugarchroll, 48
- UsUnemp, 80

- VAR.boot, 73, 87
- VAR.boot (VAR.sim), 80
- VAR.sim, 73, 80, 87
- VARrep, 28, 46, 47, 82
- VARselect, 25
- VECM, 13, 18, 23, 28, 33, 47–51, 53, 75, 76, 82, 83, 86, 87
- VECM.boot (VECM.sim), 85
- VECM.sim, 85
- VECM_symbolic, 88

- zeroyld, 77, 89