General information

The exercise sessions will be held as blackboard sessions, where the participants will present their solutions to the group. As such, the problems should be set up and solved before the session. The focus of the exercises lies on analyzing and discussing the task at hand together with the group: thus, a perfect solution is not required to be awarded points. A point will be awarded for each question, and a person will be chosen to present their solution from the pool.

Exercise 1.

Equilibrium of magnetic fusion devices

The equations describing the equilibrium properties of all magnetic configurations of fusion interest are [1]:

MHD momentum equation (Newton II):
$$\rho \frac{\mathrm{d}\mathbf{v}}{\mathrm{d}t} = \mathbf{J} \times \mathbf{B} - \nabla p \to \mathbf{J} \times \mathbf{B} = \nabla p \qquad (1)$$

Ampère's law:
$$\nabla \times \mathbf{B} = \mu_0 \mathbf{J} \tag{2}$$

Gauss' Law for magnetism:
$$\nabla \cdot \mathbf{B} = 0$$
, (3)

where the equivalence is due to the equilibrium assumption $(\partial/\partial t = 0)$, ρ is the density, **v** the velocity, **J** the current density, **B** the magnetic field, and p the plasma pressure.

- (a) Using equation (1), show that the magnetic field lines must lie in surfaces of constant pressure, i.e. that the pressure gradient is perpendicular to the magnetic field **B**.
- (b) Using equation (1) and a similar method as in a), show that the current lines must lie in surfaces of constant pressure.
- (c) Using equations (1)-(3), derive equation

$$\nabla \left(p + \frac{B^2}{2\mu_0} \right) - \kappa \frac{B^2}{\mu_0} = 0. \tag{4}$$

Use the Ampère's law to eliminate **J** from the MHD momentum balance equation. Then use the vector identity, $(\nabla \times \mathbf{B}) \times \mathbf{B} = (\mathbf{B} \cdot \nabla) \mathbf{B} - \nabla \left(\frac{B^2}{2}\right)$, to derive the force balance equation in terms of the thermal pressure gradient of the plasma, ∇p , the magnetic pressure gradient in the plasma $\nabla \frac{B^2}{2\mu_0}$, and the magnetic tension of the plasma $\kappa \frac{B^2}{\mu_0}$. $\kappa = \mathbf{b} \cdot \nabla \mathbf{b}$ is the curvature vector of the magnetic field, and **b** is the unit vector of the magnetic field. κ points towards the local center of curvature of **B**, and its magnitude is equal to the inverse radius of curvature.

(d) Shortly explain the physical interpretation of equation (4). The plasma pressure p represents the thermal energy of the plasma, but what are the meaning of the other two terms in the equation?

Exercise 2.

Pressure driven instabilities

Instabilities driven primarily by the pressure gradient in the plasma are typically classified either as interchange modes or ballooning modes [1]. Start by investigating the somewhat amusingly named sausage mode. Consider a straight plasma cylinder at equilibrium with a radius, a, a plasma pressure, p, and a current running only in the direction parallel to the axis of the cylinder. The axial magnetic field is assumed to be zero in this exercise (i.e. the magnetic field in the direction of the cylinder axis $B_z = 0$).




Figure 1: Sausage instability in a cylindrical plasma.

- (a) Using Ampere's law, show that the poloidal magnetic field, B_{θ} , scales as $\propto 1/r$.
- (b) Next, consider a radially narrowing, "sausage like", perturbation, as presented on figure Fig. 1. If we assume the pressure to remain constant, what happens to the equilibrium in the "waist" of the perturbation? How could you compensate for this instability?

Exercise 3.

Current-driven instabilities

Instabilities driven by the current density parallel to the magnetic field are often called kink modes [1], which will be treated next. Consider a pressure-less plasma cylinder ($p = 0 \rightarrow \beta = 0$), where a surface current layer on the surface of the cylinder, r = a, separates a purely axial magnetic field inside the cylinder, $(0, 0, B_z)$, r < a, from a purely poloidal magnetic field outside the cylinder, $(0, B_\theta a/r, 0)$, r > a, (lecture slides 9 - 11 'Tokamaks Part B'). B_z and B_θ are constants.

- (a) Consider a "kink like" perturbation of the plasma column, as in figure Fig. 2. What happens on the inside/outside of the bend? What are the stabilizing and destabilizing forces in this case?
- (b) Consider a tokamak, which has both a poloidal and a toroidal field. Based on your reasoning in part a, which one of them is the stabilizing one against kink perturbations?
- (c) The experimentally measured energy confinement time τ_E is nearly linearly proportional to the toroidal current in tokamaks. Why is it not a feasible strategy to simply increase the toroidal current to achieve a sufficient τ_E for ignition?




Figure 2: Kink mode in a cylindrical plasma.

Exercise 4. Ideal modes, resistive modes, and edge localized modes.

(a) Can you explain the physical difference between ideal and resistive modes? How do the resistive modes impact the magnetic geometry, and what implications do they have for the operation of a tokamak?




Figure 3: Plasma pressure profiles for L-mode (blue) and H-mode (red), and the associated ELM relaxation (green). Figure credit goes to DIFFER.

(b) Under certain conditions, the performance of a tokamak can improve suddenly when the heating power is increased. This transition from low confinement mode (L-mode) to high confinement mode (H-mode) is dubbed the L-H transition, and it is currently a crucial principle in achieving high pressures in tokamak plasmas.

As illustrated in figure 3, the transition is identified by a significant increase in plasma pressure in the core plasma and strong gradient in plasma pressure on the edge. This "edge transport barrier", however, is not inherently stable. Edge localized mode (ELM) instabilities lead to a (partial) relaxation of the gradient and thus a significant amount of heat is launched at the wall. After the energy is released, the gradient (the barrier) builds up again and this leads to a new relaxation event, creating a cyclical instability.

Type-I ELMs are the standard, large ELMs associated with a standard, high performance, high confinement mode plasmas. In an ITER-sized device with the expected edge plasma parameters in ITER, the extrapolated size of type-I ELMs can be about 20% of the energy stored in the steep gradient region at the edge, called the pedestal [2]. The melting temperature threshold of the divertor components in ITER determines the tolerable heat impact to be about $\Delta W/\sqrt{t} < 20-40~{\rm MW~s^{1/2}~m^{-2}}$, where ΔW represents the power flux density impacting the surface component, and t is the characteristic time scale of the situation [3]. Estimate this heat impact parameter for a type-I ELM in ITER, assuming:

- the stored pedestal energy in ITER is about 120 MJ.
- 65 % of the ELM energy reaches the high heat flux areas in the divertor chamber.
- the effective plasma wetted area is about 3 m³.
- the effective ELM duration is about 0.5 ms. A very nice review of ELMs in tokamaks can be found in [2].

What is your conclusion about type-I H-mode operation in ITER, can the device absorb the exhausted power?

References: [1] J.P. Freidberg, *Plasma Physics and Fusion Energy*, Cambridge University Press, 2007

[2] K. Kamiya, et al., Edge localized modes: recent experimental findings and related issues, Plasma Phys. Control. Fusion, 49, (2007), S43 – S62

[3] A. Herrmann, Overview on stationary and transient divertor heat loads, Plasma Phys. Control. Fusion, 44, (2002), 883 – 903.