Groundwater, its treatment and protection

Harri Mattila, 2021


Principal Research Scientist at Häme University of Applied Sciences, HAMK (<u>www.hamk.fi</u>)


D.Tech. (civil engineering)
Associate Professor at TUNI (decentralized water services)


General

- Groundwater forms only 0,53 % of all water resources (worldwide).
- In Finland, more than 2/3 of all raw water is groundwater or artificial groundwater
- Advantages of groundwater when compared to surface water:
 - No need for disinfection (in normal situations)
 - Temperature is rather constant (and low)
 - Little or no chemicals involved in treatment

The hydrological cycle









Observation tube (well)

- Usually PVC pipe
- DN > 50 mm
- Screen in the depth of the groundwater layer



An example of groundwater depth variations (Tuusula, Finland)



The need for groundwater treatment

- optimum situation: no treatment
- most common reason is prevention of corrosion
- Fe or Mn (in Finland)
- organic material
- fluoride
- salts
- radon
- arsenic



eulsv-Hq

- Depends on soil around the groundwater well
- Sometimes rain water can be acidic
- pH of groundwater in Finland is normally between 5 - 7

Nitrate compounds

- ammonium, nitrate, nitrite, nitrogen
- Very rarely in Finnish groundwaters
- Usually means pollution by agriculture or industry
- Sometimes also because of wastewater in groundwater!

Sulfate

- Can be diluted in groundwater for example from minerals rich of sulphur beacause of high pH.
- Important factor in corrosion
- limit 50 mg/l

Iron and manganese

- Most common problems in groundwater (specially in Finalnd)
- No health hazard technical and/or aesthetical problems
- Arr Fe < 0,2 mg/l, Mn < 0,05 mg/l
- Causing also sedimentation in networks and that's why harmful

Chloride

- Normally because of nearby sea but also because of deicing in winter
- In nature < 10 mg/l, taste limit 200 300 mg/l, recommended maximum 250 mg/l, target 25 mg/l
- Very important factor in corrosion

Hardnes

- Ca- ja Mg –salts
- $1 \text{ mmol/l} = 5.6 ^{\circ} \text{ dH}$
- □ Should be $3 5^{\circ}$ dH
- The most interesting parameter to customers due to washing machines
- sometimes high also in Finland, even >10

Aluminium

- Can be diluted from from the soil (like Fe and Mn), specially when the soil in acidic
- The maximum limit allowed 0,2 mg/l

Arsenic

- carcinogenic, max allowed 0,01 mg/l
- Mainly in deep boreholes
- In Finland about 7% of all the deep wells are contaminated

Boron

- Max allowed 1,0 mg/l
- Is indicating pollution by wastewater
- Appears very seldom

Fluoride

- WHO: max allowed 1,5 mg/l (note, drinking water should have 0,5 mg/l)
- Defluoridation is considered as an expensive task => 1. change the source if possible, 2. dilute water with another one with less flouride, 3. treatment

Copper

- Max allowed 2,0 mg/l (an average / week)
- Rather seldom in groundwater
- Mainly because of corrosion in pipelines (green colour on basins)

Bacteria

E.coli is the most important indicator

Viruses

 Very difficult to analyze => difficult to separate/destroy from water

Dilutants

- Altogether about 70 compounds
- Hydrogarbons, alcohols, aethers, esters, aldehydes, ketones

MTBE, TAME

- Additives in petrol
- Are diluted very easily in water => the first compounds found in case of pollution
- Easy to detect by smell and taste (0,03 mg/l)

Pesticides

- Hundreds of compounds
- Max allowed 0,0005 mg/l (total)
- The smallest amounts which can be detected are normally 0,00001 0,00002 mg/l

Radioactivity

- Mostly in deep wells (in the rock)
- No smell, no colour, no taste!
- Radon is the most common one in groundwater
- Max allowed 1000 Bq/l)
- => 1. new water source, 2. treatment (aeration, active carbon filtration)

Uranium


- Lack of knowledge concerning health effects
- Earlier max by WHO 0,15 mg/l, today 0,002 mg/l

Corrosion

- pH > 7,5
- calsium > 10 mg/l
- oxygen > 2 mg/l

Maps and aerial photographs

- Swamps, springs, ditches, etc.
- Humidity changes out of photgraphs
- Old maps might give valuable information



Geophysical methods

- Seismic sounding
- Electrical probing (resistance)

Drillings

- Manually
- Machinery



Iron and manganese

- Most common quality problem with ground waters
- Coagulation happens immediately with ozygen
- Iron can be removed also biologically

Removal of Fe and Mg

- In small scales
 - aeration
 - sand filtration
 - ion exchange processes
- Lime stone filtration
- Slow sand filtration

Slow sand filtration

- Water is filtered slowly through a sand layer
- Surface load 0,05 0,2 m/h
- Water per one 1 m2: 50 200 l/h
- Iron content max 1mg/l
- Pretreatment could be done by a filter containing crushed stone

Sand filtration

- Aeration needed almost always
- Dissolved iron is oxidized => can be filtered out of water
- Surface load normally 4 5 m/h
- Small filters require backwashing more often
- Might be expensive ?

UV desinfection

- Generally, ground water is microbiologically clean
- Sometimes we have experienced pollution
- UV-desinfiction is applicable method for ground waters (no turbidity nor colour)
- UV-desinfection is not affecting the taste of water unlike chlorination
- Note: in Finland, all water utilities must prepare themselves for disinfection

Ground water protection!





